Product data sheet Characteristics

RSZE1S35M

socket RSZ - separate contact - < 250 V AC - screw connector

Product availability: Stock - Normally stocked in distribution facility

Price*: 4.80 USD



Main

		<u>_</u>
Range of product	Zelio Relay	7
Product or component type	Socket	
Contact terminal arrangement	Separate	‡ 'C
Product compatibility	Plug-in relay RSB (1 C/O)	:-
Shape of pin	Flat	<u> </u>
Device short name	RSZ	
Sale per indivisible quantity	10	

Complementary

[Ith] conventional free air thermal current	12 A		
System Voltage	< 250 V AC		
Tightening torque	<= 7.08 lbf.in (0.8 N.m) (M3 screw(s))		
Fixing mode	By screw mounting on panel Clip-on mounting on 35 mm symmetrical DIN rail		
Marking	CE		
Width	0.61 in (15.5 mm)		

Environment

LITTION		3
Connections - terminals Screw connectors, flexible cable with cable end 1 x 0.251 x 2.5 mm² / AWG 22AV Screw connectors, flexible cable with cable end 2 x 0.252 x 1 mm² / AWG 22AV Screw connectors, solid cable without cable end 1 x 0.51 x 2.5 mm² / AWG 20AV Screw connectors, solid cable without cable end 2 x 0.52 x 1.5 mm² / AWG 20AV		
Standards	IEC 61984	
roduct certifications CSA UL		
Ambient air temperature for storage	-40185 °F (-4085 °C)	
Ambient air temperature for storage	-40103 T (-4003 C)	

Ambient air temperature for operation	-13185 °F (-2585 °C)
IP degree of protection	IP20 conforming to EN/IEC 60529
Dielectric strength	2500 V

Ordering and shipping details

Category	21128 - ZELIO ICE CUBE RELAY ACCESSORIES		
Discount Schedule	CP2		
GTIN	00785901618188		
Nbr. of units in pkg.	10		
Package weight(Lbs)	7.00000000000007E-2		
Returnability	Υ		
Country of origin	CN		

Contractual warranty

Warranty period	18 months	