Product data sheet Characteristics

HDA36110

PowerPact H I-Line Circuit Breaker, ThermMagn, 110A, 3P, 600V, 14kA

Product availability: Stock - Normally stocked in distribution facility





Price*: 2730.00 USD



Main

Wilder		
Product or component type	Circuit breaker	
Range of product	PowerPact H	
Trip unit technology	Thermal-magnetic	
Breaking capacity code	D	

Complementary

ETT The		
E30		:
1		
-		
		!
		1
Main		
Product or component type	Circuit breaker	
Range of product	PowerPact H	
Trip unit technology	Thermal-magnetic	
Breaking capacity code	D	
Complementary		
Line Rated Current	110 A	<u></u>
Poles description	3P	
Breaking capacity	18 kA at 480 V AC	
Dieaking Capacity	25 kA at 240 V AC	
	14 kA at 600 V AC	-
	20 kA at 250 V DC	
System Voltage	250 V DC 600 V AC	:
Mounting mode	I-Line	 :
Mounting mode		
Electrical connection	I-Line connection line Lugs load	
AWG gauge	AWG 14AWG 3/0 (aluminium/copper)	<u> </u>
Phase connection	ABC	
Magnetic hold current	900 A	.
Magnetic tripping current	1700 A	
magnetic tripping current	17007	
		•
Environment		
Product certifications	IEC	
	UL listed CE	
	CSA	i
Ambient air temperature for operation	104 °F (40 °C)	
lul 07 2047		i

Environment

		ഉ
Product certifications	IEC	Ę
	UL listed	ğ
	CE	дis
	CSA	Ē.
Ambient air temperature for operation	104 °F (40 °C)	sclain——

Ordering and shipping details

Category	01112 - HD, JD I-LINE BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901422273
Nbr. of units in pkg.	1
Package weight(Lbs)	5.46
Returnability	Υ
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0832 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Warranty period	18 months	