

Combination Type Lugs

Type XLH

Features:

- Each fitting takes a range of cable sizes.
- Equipped with brass screws and brass or bronze pressure plates on XLH011 and larger.
- Castings are of high conductivity copper alloy and are so designed, that high clamping pressure can be exerted, and maximum surface contact is provided with the wires throughout the specified range.

Material:



Cast Copper alloy body and Brass screws.
Brass or Copper alloy pressure plates.

Third Party Certification:



UL Listed: E-7512

Applicable Third Party Standards:

UL Standard: 486A
Fed. Spec: W-S-610



Type XLH



Catalog Number	XLH – Hex Head Screw												
	Conductor Range AWG/kcmil		No. of Holes	B	Dimensions in Inches					H	J	T	Hex Wrench Size
	Min.	Max.			C	D	E	F					
XLH011	4	1	1	5⁄8	3⁄4		3⁄8	9⁄32	1⁹⁄16	1¼	7⁄32	*	
XLH012	4	1	2	5⁄8	1⁷⁄16	¾	5⁄16	9⁄32	2¼	1¼	7⁄32	*	
XLH221	1	2/0	1	1³⁄16	1⁵⁄16		7⁄16	1³⁄32	1⁷⁄8	1⅝	¼	¼	
XLH222	1	2/0	2	1³⁄16	1¹⁵⁄16	1	7⁄16	1³⁄32	2⅞	1⅝	¼	¼	
XLH241	2/0	4/0	1	1	1³⁄16		9⁄16	1³⁄32	2¼	1⅝	9⁄32	5⁄16	
XLH242	2/0	4/0	2	1	1¹⁵⁄16	1	7⁄16	1³⁄32	3	1⅝	9⁄32	5⁄16	
XLH301	4/0	300	1	1¼	1⁷⁄16		1¹⁄16	1⁷⁄32	2⅝	1¾	9⁄32	5⁄16	
XLH302	4/0	300	2	1¼	2	1	7⁄16	1³⁄32	3⅜	1¾	9⁄32	5⁄16	
XLH501	300	500	1	1⅝	1⅝		1³⁄16	1⁷⁄32	3	2¹⁄16	⅜	⅜	
XLH502	300	500	2	1⅝	1¹⁵⁄16	1	7⁄16	1³⁄32	3⅝	2¹⁄16	⅜	⅜	
XLH751	500	750	1	1¾	2		1	1⁷⁄32	3¹¹⁄16	2½	1³⁄32	⅜	
XLH752	500	750	2	1¾	2¹³⁄16	1½	5⁄8	1⁷⁄32	4½	2½	1³⁄32	⅜	
XLH921	750	1000	1	2	2¼		1⅝	2¹⁄32	4¼	2¹¹⁄16	7⁄16	⅜	
XLH922	750	1000	2	2	2¾	1½	5⁄8	1⁷⁄32	4¾	2¹¹⁄16	7⁄16	⅜	