

JUNO[®]

Project: _____

Fixture Type: _____

Location: _____

Contact/Phone: _____

TRAC-MASTER[®]

Wall Wash/Floods

T5HO SERIES CLOSE-TO-TRAC MOUNT

T5T

PRODUCT SPECIFICATIONS

Lamp Two 24W, 39W or 54W high lumen T5 High Output fluorescent lamps by GE, Philips, or Osram-Sylvania • Miniature bi-pin base.

Sockets Spring-loaded sockets with 90° rotor lock allow for lamp tolerances and simplify lamp installation • Spaced apart to enable easy lamp replacement without tools.

Aiming 90° vertical aiming capability.

Connections Two standard trac adapters.

Juno Universal Trac Adapter Universally compatible with both Trac-Master 1-circuit or 2-circuit trac, Trac-Lites trac, monopoints and special mountings • Also UL Recognized for use on ConTech[®] LT Series track • Copper alloy contacts provide precise spring action - no arcing and will not take a set • True, positive electrical ground • On/off switch included • Patented embossed polarity arrows on bottom of adapter • Spring-loaded positive latch with embossed polarity arrows secures trac light to trac • Two-position power contact provided for two-circuit application.

Alternate TEK/HTEK Trac Adapter Compatible with either Juno TEK or HTEK trac systems • System specific and assembled to trac fixture • Integrally polarized construction to prevent reverse installation – only allows insertion in proper orientation • Rotary circuit selector enables simple switching between circuits • Integral on/off switch enables individual fixtures to be switched for servicing.

Alternate HTYPE Trac Adapter Compatible with track systems which use a H-type track adapter, including Lithonia LTS Decorative Track (not LT type) • System specific and assembled to trac fixture • Two-position power contact provided for two-circuit application • Consult factory for additional information.

Housing Extruded aluminum channel with die-cast aluminum end caps • Rich, textured paint in a variety of finishes.

Reflector Computer designed specifically for T5HO lamps to offer optimum performance • Specification grade, highly reflective and minimally diffuse aluminum material provides wide, uniform beam pattern with optimized intensity, minimal glare and peak operating efficiency.

Ballast HPF Electronic 120V • End of lamp life protection.

Louwer Precision formed, brushed stainless steel blades provide shielding • Thin cross section maximizes light output • Clear cathodic electropaint finish maintains appearance with low maintenance • Attaches without tools to facilitate installation and lamp replacement • Included on all models.


Lamp Containment Barrier Food service compliant lens/barrier made from clear extruded acrylic • Attaches without tools via permanently mounted spring clips to facilitate installation and lamp replacement • Sold as an optional accessory.

Labels UL listed • CSA certified • Union made • Assembled in U.S.A. Specifications subject to change without notice.


DIMENSIONS





T5T 2FT



T5T 3FT



T5T 4FT



ENGINEERING DATA

	T5T 2FT	T5T 3FT	T5T 4FT
Input Voltage	120V	120V	120V
Total Input Power	59W	89W	120W
Operating Amps	0.51A	0.75A	1.03A
Power Factor	>0.98	>0.98	>0.98
T.H.D.	<10%	<10%	<10%
Min. Starting Temp.	0°F	0°F	0°F
Crest Factor	<1.7	<1.7	<1.7
Ballast Factor	1.0 Typ.	1.0 Typ.	1.0 Typ.
Sound Rating	A	A	A

ConTech is a registered trademark of ConTech Lighting.

AcuityBrands

1300 S. Wolf Road • Des Plaines, IL 60018 • Phone (847) 827-9880 • Fax (847) 827-2925 • Visit us at www.acuitybrands.com/juno-trac
Printed in U.S.A. ©2017-2018 Acuity Brands Lighting, Inc. Rev. 05/6/18

TRAC-MASTER®

Wall Wash/Floods

T5HO SERIES CLOSE-TO-TRAC MOUNT

T5T

ORDERING INFORMATION

Ordering Examples: T5T 2FT WH, T5T TEK 4FT BL

Series	Mounting Adapter Type	Nominal Length	Finish
T5T T5HO Wall Wash/Floods	(Blank) Universal 120V Trac Adapter	2FT 2 FT Nominal Length	WH White
	HTEK HTEK 277V Trac Adapter	3FT 3 FT Nominal Length	BL Black
	TEK TEK 120V Trac Adapter	4FT 4 FT Nominal Length	SL Silver
	HTYPE H-Type Trac Adapter		

Accessories	
T5L 2FT CLR	2' Acrylic Lens, Clear
T5L 3FT CLR	3' Acrylic Lens, Clear
T5L 4FT CLR	4' Acrylic Lens, Clear


TRAC-MASTER®


Wall Wash/Floods


T5HO SERIES CLOSE-TO-TRAC MOUNT


T5T


T5HO FLOOD/WALL WASH


T5T 2FT	Distance from ceiling	Single Fixture Performance					Multiple Fixture Performance						
		0	1'	2'	3'	4'	5'	←4'→	←6'→	←8'→			
TRAC 2" FROM WALL	□												
	1'	167	116	43	13	4	1	176	88	176	169	34	169
	2'	108	83	42	17	6	3	121	86	121	111	26	111
	3'	54	45	28	15	7	3	69	59	69	57	30	57
	4'	29	25	18	11	6	3	42	39	42	33	22	33
	5'	17	15	11	8	5	3	28	27	28	21	17	21
	6'	10	9	8	6	4	3	20	19	20	14	12	14
Two 24W T5HO Lamps 3,520	7'	7	6	5	4	3	2	14	14	14	10	9	10
Total Lumens	8'	5	4	4	3	2	2	11	10	11	7	7	7
	9'	3	3	3	2	2	2	8	8	8	6	5	6

T5T 2FT	Distance from ceiling	Single Fixture Performance					Multiple Fixture Performance						
		0	1'	2'	3'	4'	5'	←4'→	←6'→	←8'→			
TRAC 3" FROM WALL	□												
	1'	77	60	32	14	6	3	89	67	89	77	39	77
	2'	72	60	37	19	9	4	92	78	92	79	29	79
	3'	51	44	30	18	10	5	73	67	73	57	37	57
	4'	33	30	22	15	9	5	53	50	53	39	30	39
	5'	20	18	15	11	7	5	37	36	37	26	23	26
	6'	13	23	10	8	6	4	27	27	27	20	18	20
Two 24W T5HO Lamps 3,520	7'	9	9	7	6	5	3	21	20	21	15	14	14
Total Lumens	8'	6	6	5	5	4	3	16	16	16	11	11	11
	9'	5	4	4	3	3	2	12	12	12	9	9	9

T5T 3FT	Distance from ceiling	Single Fixture Performance					Multiple Fixture Performance						
		0	1'	2'	3'	4'	5'	←6'→	←8'→	←10'→			
TRAC 3" FROM WALL	□												
	1'	117	99	59	27	12	5	122	55	122	118	35	118
	2'	117	102	67	36	17	8	125	73	125	119	23	119
	3'	81	72	52	32	18	10	91	66	91	84	36	84
	4'	54	49	38	26	16	10	66	54	66	57	33	57
	5'	34	31	26	19	13	9	45	41	45	38	27	38
	6'	22	21	18	14	10	7	33	31	33	27	22	27
Two 39W T5HO Lamps 6,160	7'	15	15	13	11	8	6	25	25	25	20	18	20
Total Lumens	8'	11	11	10	8	7	5	20	19	20	16	14	16
	9'	8	8	7	6	5	4	16	16	16	13	12	13

T5T 3FT	Distance from ceiling	Single Fixture Performance					Multiple Fixture Performance						
		0	1'	2'	3'	4'	5'	←6'→	←8'→	←10'→			
TRAC 4" FROM WALL	□												
	1'	104	92	65	38	21	11	115	79	115	107	42	107
	2'	91	82	61	39	23	12	105	81	105	96	46	96
	3'	72	66	51	35	22	13	88	73	88	77	45	77
	4'	49	45	37	27	18	12	65	58	65	55	38	55
	5'	34	32	27	21	15	10	50	46	50	41	31	41
	6'	24	23	20	16	12	9	38	36	38	30	25	30
Two 39W T5HO Lamps 6,160	7'	17	16	14	12	9	7	29	28	29	23	20	23
Total Lumens	8'	12	12	11	9	7	6	23	22	23	18	16	18
	9'	9	9	8	7	6	5	18	18	18	14	13	14

T5T 4FT	Distance from ceiling	Single Fixture Performance					Multiple Fixture Performance						
		0	1'	2'	3'	4'	5'	←6'→	←8'→	←10'→			
TRAC 3" FROM WALL	□												
	1'	148	132	90	46	20	8	156	93	156	150	40	150
	2'	152	137	99	57	29	14	165	116	165	155	58	155
	3'	107	98	75	49	28	15	124	100	124	112	57	112
	4'	72	67	54	38	25	15	91	80	91	78	50	78
	5'	46	43	36	27	19	13	64	60	64	53	40	53
	6'	31	29	25	20	15	11	47	45	47	38	32	38
Two 54W T5HO Lamps 8,800	7'	21	21	18	15	12	9	36	35	36	29	25	29
Total Lumens	8'	15	15	13	11	9	7	28	28	28	22	21	22
	9'	11	11	10	9	7	6	23	23	23	18	17	18

T5T 4FT	Distance from ceiling	Single Fixture Performance					Multiple Fixture Performance						
		0	1'	2'	3'	4'	5'	←6'→	←8'→	←10'→			
TRAC 4" FROM WALL	□												
	1'	137	125	94	59	33	17	155	121	155	142	66	142
	2'	122	112	87	58	35	20	144	121	144	129	71	129
	3'	97	90	73	51	33	20	122	108	122	106	68	106
	4'	66	62	52	39	27	18	91	84	91	76	56	76
	5'	47	45	38	30	22	15	70	67	70	57	46	57
	6'	33	32	28	23	17	13	54	52	54	43	37	43
Two 54W T5HO Lamps 8,800	7'	23	23	20	17	14	10	42	41	42	32	30	32
Total Lumens	8'	17	17	15	13	11	8	33	32	33	25	24	25
	9'	13	12	11	10	8	7	26	26	26	20	19	20