# Eaton DH321FDK

## Catalog Number: DH321FDK

Eaton Heavy duty single-throw fused safety switch, 30 A, NEMA 12/3R, Painted galvanized steel, Class H, Fusible without neutral, Three-pole, Three-wire, 240 V, Max Hp: 1.5, 3/ 7.5 hp (1,3PH Std/3PH TD), #14-#2 Cu/Al

## General specifications

Product Name Eaton heavy duty fusible safety switch

#### UPC

782113205410

Product Height 8.5 in

0.0 ...

Product Weight 22 lb DH321FDK Product Length/Depth 20 in

Product Width 9.5 in

Catalog Number

#### Warranty

Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Compliances NEC 230.62 (C) Compliant Barrier Certifications UL Listed

#### Catalog Notes

Suitable for service entrance use with a neutral or ground lug kit installed. Can be field modified to meetNEMA 3R rainproof requirements when a factory provided drain hole is opened.





## **Physical Attributes**

#### Enclosure

NEMA 12, NEMA 3R

Enclosure material Painted galvanized steel

Fuse class provision Class H

Fuse configuration Fusible without neutral

Number Of Poles Three-pole

Number of wires

3

Type Heavy duty fusible safety switch

Wire size #14-2 AWG Cu/Al

## Performance Ratings

Amperage Rating

30A

HP rating - max 1.5, 3/ 7.5 hp (1,3PH Std/3PH TD)

NEMA rating NEMA 12/3R

Voltage rating

240V

## Miscellaneous

Product Category Heavy Duty, Fusible without neutral

### Resources

Catalogs Eaton's Volume 2—Commercial Distribution

Drawings 30and60A 3POLE FUSIBLE T12

Specifications and datasheets Eaton Specification Sheet - DH321FDK



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia