Eaton DH221NDK

Catalog Number: DH221NDK

Eaton Heavy duty single-throw fused safety switch, Enhanced visible blade, 30 A, NEMA 12/3R, Class H, neutral, Two-pole, Three-wire, 240 V, Max Hp: 1.5, 3 hp/3, 7.5 hp/5 hp (1,3PH @ Std fuse/time delay/250 Vdc), #14-#2 Cu/Al

General specifications



Eaton heavy duty fusible safety switch

Product Length/Depth

DH221NDK

Catalog Number

20 in

Product Height

782113205397

8.5 in

UPC

Product Width

9.5 in

Product Weight

22 lb

Warranty

Eaton Selling Policy 25-000, one (1) year

from the date of installation of the

Product or eighteen (18) months from the

date of shipment of the Product,

whichever occurs first.

Compliances

NEC 230.62 (C) Compliant Barrier

Certifications
UL Listed

Catalog Notes

Can be field modified to meetNEMA 3R rainproof requirements when a factory provided drain hole is opened. 3-phase hp ratings shown are grounded B phase ratings; UL listed.

Powering Business Worldwide

Photo is representative

Physical Attributes

Enclosure

NEMA 12, NEMA 3R

Enclosure material

Painted galvanized steel

Fuse class provision

Class H

Fuse configuration

Fusible with neutral

Number Of Poles

Two-pole

Number of wires

3

Type

Heavy duty fusible safety switch

Performance Ratings

Amperage Rating

30A

HP rating - max

1.5, 3 hp/3, 7.5 hp/5 hp (1,3PH @ Std fuse/time delay/250 Vdc)

NEMA rating

NEMA 12/3R

Voltage rating

240V

Miscellaneous

Product Category

Heavy Duty, Fusible with neutral

Resources

Catalogs

Eaton's Volume 2—Commercial Distribution

Specifications and datasheets

Eaton Specification Sheet - DH221NDK



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia