Eaton DH262UDK

Catalog Number: DH262UDK

Eaton Heavy duty single-throw non-fused safety switch, Singlethrow, 60 A, NEMA 12, Painted galvanized steel, Non-Fusible, Two-pole, Two-wire, 10 at 240 Vac TD 1 Ph, 20 at 480 Vac TD 1 Ph, 25 at 600 Vac TD 1 Ph, 25 at 600 Vdc

General specifications



Eaton heavy duty non-fusible safety

switch

Catalog Number

DH262UDK

UPC

782113206110

Product Length/Depth

10.22 in

Product Height

14.14 in

Product Width

Product Weight

17 lb

8.76 in

Warranty

Compliances

Eaton Selling Policy 25-000, one (1) year NEC 230.62 (C) Compliant Barrier

from the date of installation of the

Product or eighteen (18) months from the

date of shipment of the Product,

Certifications

UL Listed

whichever occurs first.

Catalog Notes

Suitable for service entrance use with a neutral or ground lug kit installed. Can be field modified to meetNEMA 3R rainproof requirements when a factory provided

drain hole is opened.



Photo is representative



Physical Attributes

Enclosure

NEMA 12

Enclosure material

Painted galvanized steel

Fuse configuration

Non-fusible

Number Of Poles

Two-pole

Number of wires

2

Type

Single-throw

Performance Ratings

Amperage Rating

60 A

HP rating - max

10 at 240 Vac TD 1 Ph, 20 at 480 Vac TD 1 Ph, 25 at 600 Vac TD 1 Ph, 25 at 600 Vdc

NEMA rating

NEMA 12, NEMA 3R

Voltage rating

600 V

Miscellaneous

Product Category

Heavy Duty, Non-Fusible

Resources

Catalogs

Eaton's Volume 2—Commercial Distribution

Specifications and datasheets

Eaton Specification Sheet - DH262UDK

Warranty guides

Selling Policy 25-000 - Distribution and Control Products and Services

Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.









Eaton.com/socialmedia

