Eaton DH322NDK

Catalog Number: DH322NDK

Eaton Heavy duty single-throw fused safety switch, 60 A, NEMA 12/3R, Painted galvanized steel, Class H, Fusible with neutral, Three-pole, Four-wire, 240 V, Max Hp: 3, 7.5/ 10, 15/ 10 hp (1,3PH @Std/TD/250 Vdc), #14-#2 Cu/Al

General specifications



Eaton heavy duty fusible safety switch

DH322NDK

UPC

782113205922

Product Length/Depth

Catalog Number

20 in

Product Height

9.5 in

8.5 in

22 lb

Warranty

Product Width

Product Weight

Eaton Selling Policy 25-000, one (1) year

from the date of installation of the

Product or eighteen (18) months from the

date of shipment of the Product,

whichever occurs first.

Photo is representative

Compliances

NEC 230.62 (C) Compliant Barrier

Certifications

UL Listed

Catalog Notes

Can be field modified to meetNEMA 3R rainproof requirements when a factory provided drain hole is opened



Physical Attributes

Enclosure

NEMA 12, NEMA 3R

Enclosure material

Painted galvanized steel

Fuse class provision

Class H

Fuse configuration

Fusible with neutral

Number Of Poles

Three-pole

Number of wires

Type

Heavy duty fusible safety switch

Wire size

#14-2 AWG Cu/AI

Performance Ratings

Amperage Rating

60A

HP rating - max

3, 7.5/10, 15/10 hp (1,3PH @Std/TD/250 Vdc)

NEMA rating

NEMA 12/3R

Voltage rating

240V

Miscellaneous

Product Category

Heavy Duty, Fusible with neutral

Resources

Catalogs

Eaton's Volume 2—Commercial Distribution

Drawings

30and60A 3POLE FUSIBLE T12

Specifications and datasheets

Eaton Specification Sheet - DH322NDK



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia