Eaton DH322FDK

Catalog Number: DH322FDK

Eaton Heavy duty single-throw fused safety switch, 60 A, NEMA 12/3R, Painted galvanized steel, Class H, Three-pole, Three-wire, 240 V, Max Hp: 3, 7.5/ 10, 15/ 10 hp (1,3PH @Std/TD/250 Vdc), #14-#2 Cu/Al

General specifications

Product Name Eaton heavy duty fusible safety switch

UPC

782113205908

Product Height

8.5 in

Product Weight 22 lb DH322FDK Product Length/Depth 20 in

Catalog Number

Product Width 9.5 in

Warranty

Certifications

UL Listed

Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Compliances NEC 230.62 (C) Compliant Barrier

Catalog Notes

Suitable for service entrance use with a neutral or ground lug kit installed. Can be field modified to meetNEMA 3R rainproof requirements when a factory provided drain hole is opened.





Physical Attributes

Enclosure

NEMA 12, NEMA 3R

Enclosure material Painted galvanized steel

Fuse class provision Class H

Fuse configuration Fusible without neutral

Number Of Poles Three-pole

Number of wires

3

Type Heavy duty fusible safety switch

Wire size #14-2 AWG Cu/Al

Performance Ratings

Amperage Rating

60A

HP rating - max 3, 7.5/ 10, 15/ 10 hp (1,3PH @Std/TD/250 Vdc)

NEMA rating NEMA 12/3R

Voltage rating

240V

Miscellaneous

Product Category Heavy Duty, Fusible without neutral

Resources

Catalogs Eaton's Volume 2—Commercial Distribution

Drawings 30and60A 3POLE FUSIBLE T12

Specifications and datasheets Eaton Specification Sheet - DH322FDK



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Right Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia