

# Eaton C25END430A

Catalog Number: C25END430A

Eaton Definite purpose control contactor, Non-reversing, Four-pole, 30A, 110-120 Vac, 50/60 Hz, Open with metal mounting plate, Screw/pressure plate and quick connect terminals (side-by-side), 30A IFL, 40A RL

## General specifications



Photo is representative

<b>Product Name</b>	<b>Catalog Number</b>
Eaton definite purpose contactor	C25END430A
<b>UPC</b>	<b>Product Length/Depth</b>
782113542331	3.38 in
<b>Product Height</b>	<b>Product Width</b>
3.75 in	2.68 in
<b>Product Weight</b>	<b>Warranty</b>
2.3 lb	1 year
<b>Certifications</b>	<b>Catalog Notes</b>
CSA Certified UL Recognized	Resistive Load rating per pole

## defaultTaxonomyAttributeLabel

### Amperage Rating

30A

### Number Of Poles

Four-pole

### Type

Non-reversing

### Coil

110-120 Vac, 50/60 Hz

### Enclosure

Open with metal mounting plate

### Frame size

25-40 A, four-pole

### Inductive full load

30 A

### Model

Contactors

### Resistive load

40 A

### Terminals

Screw/pressure plate and quick connect terminals (side-by-side)

### Connection

Quick

## Resources

### Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

### Drawings

[C25END4 2D PDF](#)

[C25END4 3D Model Xchange](#)

[C25END4 AutoCAD 2D Footprint](#)

[C25END4 3D Inventor](#)

[C25END4 AutoCAD 2D Footprint \(mm\)](#)

[C25END4 2D Drawing Xchange](#)

### Specifications and datasheets

[Eaton Specification Sheet - C25END430A](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](#)