

Eaton DH324FDK

Catalog Number: DH324FDK

Eaton Heavy duty single-throw fused safety switch, 200 A, NEMA 12/3R, Painted galvanized steel, Class H, Fusible without neutral, Three-pole, Three-wire, 240 V, Max Hp: 15, 25/60/40 hp (1,3PH @Std/3PH @TD/250 Vdc), #6-250 kcmil Cu/Al



Photo is representative

General specifications

Product Name	Catalog Number
Eaton heavy duty fusible safety switch	DH324FDK
UPC	Product Length/Depth
782113206721	37.5 in
Product Height	Product Width
11.5 in	19 in
Product Weight	Warranty
55 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
Compliances	Certifications
NEC 230.62 (C) Compliant Barrier	UL Listed

Catalog Notes

Suitable for service entrance use with a neutral or ground lug kit installed. Can be field modified to meet NEMA 3R rainproof requirements when a factory provided drain hole is opened.

Physical Attributes

Enclosure

NEMA 12, NEMA 3R

Enclosure material

Painted galvanized steel

Fuse class provision

Class H

Fuse configuration

Fusible without neutral

Number Of Poles

Three-pole

Number of wires

3

Type

Heavy duty fusible safety switch

Wire size

#6 AWG-250 kcmil Cu/Al

Performance Ratings

Amperage Rating

200A

HP rating - max

15, 25/ 15, 60/ 40 hp (1,3PH @Std/TD/250 Vdc)

NEMA rating

NEMA 12/3R

Voltage rating

240V

Miscellaneous

Product Category

Heavy Duty, Fusible without neutral

Resources

Catalogs

[Eaton's Volume 2—Commercial Distribution](#)

Specifications and datasheets

[Eaton Specification Sheet - DH324FDK](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
[Eaton.com](#)

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](#)