Eaton DH224NDK

Catalog Number: DH224NDK

Eaton Heavy duty single-throw fused safety switch, Enhanced visible blade, 200 A, NEMA 12/3R, Fusible with neutral, Two-pole, Three-wire, 240 V, Max Hp: 15, 25 hp/15, 60 hp/40 hp (1,3PH @ Std fuse/time delay/250 Vdc), #6-300 kcmil Cu/Al

General specifications



Eaton heavy duty fusible safety switch

UPC

782113206707

Product Height

11.5 in

Product Weight

55 lb

Catalog Number

DH224NDK

Product Length/Depth

37.5 in

Product Width

19 in

Warranty

Eaton Selling Policy 25-000, one (1) year

from the date of installation of the

Product or eighteen (18) months from the

date of shipment of the Product,

whichever occurs first.

Compliances

NEC 230.62 (C) Compliant Barrier

Certifications

UL Listed

Catalog Notes

Can be field modified to meetNEMA 3R rainproof requirements when a factory provided drain hole is opened. 3-phase hp ratings shown are grounded B phase ratings; UL listed.



Photo is representative

Physical Attributes

Enclosure

NEMA 12, NEMA 3R

Enclosure material

Painted galvanized steel

Fuse class provision

Class H

Fuse configuration

Fusible with neutral

Number Of Poles

Two-pole

Number of wires

3

Type

Heavy duty fusible safety switch

Performance Ratings

Amperage Rating

200A

HP rating - max

15, 25 hp/15, 60 hp/40 hp (1,3PH @ Std fuse/time delay/250 Vdc)

NEMA rating

NEMA 12/3R

Voltage rating

240V

Miscellaneous

Product Category

Heavy Duty, Fusible with neutral

Resources

Catalogs

Eaton's Volume 2—Commercial Distribution

Specifications and datasheets

Eaton Specification Sheet - DH224NDK



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.









Eaton.com/socialmedia