Eaton DH364UDK

Catalog Number: DH364UDK

Eaton Heavy duty single-throw non-fused safety switch, Singlethrow, 200A, NEMA 12, Painted galvanized steel, Non-Fusible, Three-pole, Three-wire, 50 at 480 Vac TD 1 Ph, 50 at 600 Vac TD 1 Ph, 60 at 240 Vac TD 3 Ph

General specifications

Product Name Catalog Number DH364UDK Eaton heavy duty non-fusible safety switch UPC 782113206882 Product Length/Depth **Product Height** 11.5 in 34.38 in Product Width **Product Weight** 16 in 55 lb Compliances Warranty Eaton Selling Policy 25-000, one (1) year NEC 230.62 (C) Compliant Barrier from the date of installation of the Certifications Product or eighteen (18) months from the UL Listed date of shipment of the Product, whichever occurs first. **Catalog Notes**

Suitable for service entrance use with a neutral or ground lug kit installed. Can be field modified to meetNEMA 3R rainproof requirements when a factory provided drain hole is opened.



Powering Business Worldwide

Physical Attributes	Performance Ratings
Enclosure	Amperage Rating
NEMA 12	200A
Enclosure material	HP rating - max
Painted galvanized steel	50 at 480 Vac TD 1 Ph, 50 at 600 Vac TD 1 Ph, 60 at 240 Vac
Fuse configuration	TD 3 Ph, 125 at 480 Vac TD 3 Ph, 150 at 600 Vac TD 3 Ph, 40
Non-fusible	at 250 Vdc
Number Of Poles	NEMA rating
Three-pole	NEMA 12, NEMA 3R
Number of wires	Voltage rating
3 Type Single-throw	600 V Miscellaneous
	Product Category

Resources

Catalogs

Eaton's Volume 2—Commercial Distribution

Specifications and datasheets

Eaton Specification Sheet - DH364UDK



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Right Reserved.

Eaton is a registered trademark.

Heavy Duty, Non-Fusible

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia