# Eaton DH365UDK

## Catalog Number: DH365UDK

Eaton Heavy duty single-throw non-fused safety switch, Single-throw, 400 A, NEMA 12, Painted galvanized steel, Non-Fusible, Three-pole, 3-wire, 125 at 240 Vac TD 3 Ph, 250 at 480 Vac TD 3 Ph, 350 at 600 Vac TD 3 Ph, 50 at 250 Vdc

#### General specifications

Product Name

Catalog Number

Eaton heavy duty non-fusible safety

DH365UDK

switch

UPC

782113207322

Product Length/Depth

**Product Height** 

12.43 in

57.47 in

**Product Width** 

Product Weight

24.12 in

115 lb

Warranty

Compliances

Eaton Selling Policy 25-000, one (1) year NEC 230.62 (C) Compliant Barrier

from the date of installation of the

Product or eighteen (18) months from the Certifications

date of shipment of the Product,

UL Listed

whichever occurs first.

Catalog Notes

Suitable for service entrance use with a Neutral Kit installed. Can be field modified to meet NEMA 3R rainproof requirements when a factory provided drain hole is opened. Use outside poles of three-pole switch for two-pole

applications.



## **Physical Attributes**

Enclosure

NEMA 12

**Enclosure material** 

Painted galvanized steel

Fuse configuration

Non-fusible

**Number Of Poles** 

Three-pole

Number of wires

3

Type

Single-throw

## Performance Ratings

**Amperage Rating** 

400A

HP rating - max

125 at 240 Vac TD 3 Ph, 250 at 480 Vac TD 3 Ph, 350 at 600 Vac TD 3 Ph, 50 at 250 Vdc

**NEMA** rating

NEMA 12, NEMA 3R

Voltage rating

600 V

### Miscellaneous

**Product Category** 

Heavy Duty, Non-Fusible

#### Resources

#### Catalogs

Eaton's Volume 2—Commercial Distribution

#### Specifications and datasheets

Eaton Specification Sheet - DH365UDK

#### Warranty guides

Selling Policy 25-000 - Distribution and Control Products and Services

Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.











