

# Eaton C25ENF440A

Catalog Number: C25ENF440A

Eaton definite purpose contactor, Quick, 50A, 208-240 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, 50A, Contactor, Three-pole, 65A, Box lugs (posidrive setscrew) and quick connect terminals , Non-reversing

## General specifications



Photo is representative

### Product Name

Eaton definite purpose contactor

### Catalog Number

C25ENF440A

### UPC

782113475578

### Product Length/Depth

3.38 in

### Product Height

3.75 in

### Product Width

2.68 in

### Product Weight

2.15 lb

### Warranty

1 year

### Compliances

RoHS Compliant

### Certifications

CSA Certified

UL Recognized

### Catalog Notes

Resistive Load rating per pole

## defaultTaxonomyAttributeLabel

### Amperage Rating

40A

### Number Of Poles

Four-pole

### Type

Non-reversing

### Coil

24 Vac, 50/60 Hz

### Enclosure

Open with metal mounting plate

### Frame size

15-50 A, two-pole and three-pole

### Inductive full load

40 A

### Model

Contactor

### Resistive load

50 A

### Terminals

Box lugs (posidrive setscrew) and quick connect terminals (side-by-side)

### Connection

Quick

## Resources

### Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

### Drawings

[C25ENF4 2D Drawing Xchange](#)

[C25ENF4 3D Model Xchange](#)

[C25ENF4 2D PDF](#)

[C25ENF4 AutoCAD 2D Footprint \(mm\)](#)

[C25ENF4 AutoCAD 2D Footprint](#)

[C25ENF4 3D Inventor](#)

### Specifications and datasheets

[Eaton Specification Sheet - C25ENF440A](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)