


16944 - F27BXSPX30RS10PK

GE Biax® T5 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse





CAUTIONS & WARNINGS


Caution

Lamp may shatter and cause injury if broken

- Remove and install by grasping only plastic portion of the lamp.

GRAPHS & CHARTS

Graphs_Spectral Power Distribution



GENERAL CHARACTERISTICS

Lamp Type

Bulb Base Equivalent Wattage (NOM) Rated Life (NOM) Starting Temperature (MIN) Mercury Content (NOM) Picograms of Mercury (NOM) Primary Application Compact Fluorescent - Plug-In T5 4-Pin (2G11) 100.0 W 12000.0 h 10.0 °C 4.0 mg 205.7613 pg Facilities;Retail Display;Hospitality;Office;Restaurant;W

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)1800.0Mean Lumens (NOM)1620.0Nominal Initial Lumens per Watt66.66667(NOM)Color Temperature (NOM)3000.0 KColor Rendering Index (CRI)82.0(NOM)Kom

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	27.0	
Voltage (NOM)	87.0	
Lamp Current (NOM)	0.335	А

DIMENSIONS

Maximum Overall Length	12.800 in(325.1 mm)
(MOL) (NOM)	
Minimum Overall Length (NOM)	12.800 in(325.1 mm)
Nominal Length (NOM)	12.800 in(325.1 mm)
Bulb Diameter (DIA) (NOM)	3.125 in(79.4 mm)

PRODUCT INFORMATION

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC 16944 F27BXSPX30RS10PK 60501-IEC-4224-1 Master 10043168169445 40 Unit 1 40

043168169448

NOTES

• 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).

Based on 60Hz reference circuit.

• Fluorescent lamp lumens decline during life

• Life ratings for the F18BX preheat lamps are based on operating the lamp at 3 hrs per start on a preheat type circuit. Operation on rapid start and instant start ballasts is not recommended. Life ratings for all lamps are based on operating the lamp at 3 hrs per start on a rapid start type ballast. Life rating on a preheat or instant start ballast is 25% lower than other Rapid Start High Lumen Biax.