

**22865 - Q250T3/CL-6PK** GE T2.5







#### **CAUTIONS & WARNINGS**

#### Caution

- Lamp emits UV radiation which may cause eye/skin irritation. RG-1
- Minimize exposure.
- Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

## Warning

- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Burn
  - Allow lamp to cool before handling.
  - Turn power off before installing lamp.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not exceed 110% of rated voltage.
- Do not touch glass with bare hands.
- Do not use lamp if outer glass is scratched or broken.
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.

## **GENERAL CHARACTERISTICS**

Lamp Type Halogen - Double-Ended

Bulb T2.5

Base Recessed Single Contact

(R7s)
Filament C-8
Rated Life (NOM) 1500.0 h

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 4000.0 Color Temperature (NOM) 2950.0 K Nominal Initial Lumens per Watt 16.0

(NOM)

### **ELECTRICAL CHARACTERISTICS**

Wattage (NOM) 250.0
Voltage (NOM) 120.0
Burn Position Horizontal

#### **DIMENSIONS**

Maximum Overall Length 3.125 in(79.4 mm)

(MOL) (NOM)

Bulb Diameter (DIA) (NOM)0.312 in(7.9 mm)Light Center Length (LCL)1.250 in(31.8 mm)

(NOM)

# **PRODUCT INFORMATION**

Product Code 22865

Description Q250T3/CL-6PK Standard Package BUNDLE

Standard Package GTIN 30043168228658

Standard Package Quantity
Sales Unit
No Of Items Per Sales Unit
No Of Items Per Standard

144

Package

UPC 043168228657