


26805 - 65R30/FL/LL 6PK

GE soft white 65 watt R30 floodlight 1-pack

- Use original GE's Soft White when you need a light without glare and harsh shadows.
- GE's Floodlights cast a wider beam that adds drama to fireplaces, kitchen counters and entryways.
- 2600K soft white light appearance
- Estimated yearly energy costs \$7.83 based on 3 hours per day \$0.11 per kWh
- GE soft white indoor spotlights provide warm, pleasing everyday light without harsh glares and shadows. These bulbs' funnel shape and reflective coating help direct light where it is needed better than a standard incandescent bulb
- Lasts 2.3 years based on 3 hours per day usage
- R30 indoor floodlight with medium base for use in directional fixtures such as recessed can lighting
- 670 lumens providing comfortable, inviting™ light













CAUTIONS & WARNINGS

Warning

- Unexpected lamp rupture may cause injury, fire, or property damage
- Avoid direct water, liquid or metal contact.
- Risk of Fire
- Keep combustible materials away from lamp.

*Twenty month life based on rated life at 4 hours/day. Provides nearly the same light output (725 lumens) as the 65 watt R30 Soft White (2000 hrs. rated life, 755 lumens).

GENERAL CHARACTERISTICS

Lamp Type Incandescent - Reflector

Bulb BR30

Base Medium Screw (E26)

Filament CC-6
Rated Life (NOM) 2500.0 h
Life in Years (NOM) 2.3

Primary Application Indoor Floodlight

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 670.0 Color Temperature (NOM) 2600.0 K Nominal Initial Lumens per Watt 11.15385

(NOM)

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 65.0
Voltage (NOM) 120.0
Estimated Energy Cost per 7.83
Year (NOM)

DIMENSIONS

Maximum Overall Length 5.370 in(136.4 mm)

(MOL) (NOM)

Bulb Diameter (DIA) (NOM) 3.750 in(95.2 mm)

PRODUCT INFORMATION

Product Code 26805

Description 65R30/FL/LL 6PK

Standard Package BUNDLE Standard Package GTIN 00043168268059

Standard Package Quantity 30
Sales Unit Unit
No Of Items Per Sales Unit 1
No Of Items Per Standard 30

Package

UPC 043168118613