

31074 - GE Protected ConstantColor® CMH® Ceramic Metal Halide

CMH70/O/UVC/U/942/MED/D

GENERAL CHARACTERISTICS

Base Description Medium Screw

Base Temp C-degrees (MAX) 190 °C
Base Type Screw-In

Lamp Enclosure Type (LET) Open or enclosed fixtures

Mercury-Picogrm per mean Im hr123.3Rated Life Hours-nominal15000 hBulb Finishes and ColorsCoatedMercury Content EMEA ONLY17.4Bulb MaterialHard glass

Product Technology High Intensity Discharge

Base E26 Bulb Shape ED17

PHOTOMETRIC CHARACTERISTICS

Effective Arc Length 0.28125 in
Mean Lumens nominal 4000 lm
Nominal Lumens per Watt 74 lm
Initial Lumens-nominal 5200 lm
Color Rendering Index-CRI 90
Color Temperature 4000 K

PRODUCT INFORMATION

Product Code 31074

Description CMH70/O/UVC/U/942/MED/D

Alternative Unit Of Measure CASE

Standard Package Quantity

Ean UPC 043168310741 Standard Package GTIN 10043168310748

No Of Items Per Sales Unit

No Of Items Per Standard Package

Sales Unit Case

UCC 043168310741

Alternative Unit Of Measure EACH
Standard Package Quantity 6

Ean UPC 043168310741 Standard Package GTIN 00043168310741

No Of Items Per Sales Unit 1
No Of Items Per Standard Package 6
Sales Unit Each

UCC 043168310741

DIMENSIONS

Diameter 2.13 in Light Center Length Millimeter 3.38 in Nominal Length 5.43 in

ELECTRICAL CHARACTERISTICS

Burn Position Universal burning position

Hot Restart Time to 90%MAX 15 min Rated power (Watts) 70 W

CAUTIONS & WARNINGS

WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information: http://www.fda.gov/cdrh/radhealth/products/urburns.html

Caution

Lamp may shatter and cause injury if broken

Dispose of lamp in a closed container.

Do not use excessive force when installing lamp.

Do not use lamp if outer glass is scratched or broken.

Warning

Risk of Burn

Allow lamp to cool before handling.

Do not turn on lamp until fully installed.

A damaged lamp emits UV radiation which may cause eye/skin injury

Turn power off if glass bulb is broken. Remove and dispose of lamp.

Risk of Fire

Keep combustible materials away from lamp.

Use in fixture rated for this product.

Risk of Electric Shock

Do not use where directly exposed to water or outdoors without an enclosed fixture.

Turn power off before inspection

installation or removal.

Unexpected lamp rupture may cause injury, fire, or property damage

Do not exceed rated voltage.

Do not store flammable materials near/below S-rated lamp in open fixture

Do not turn on lamp until fully installed.

Do not use beyond rated life.

Do not use lamp if outer glass is scratched or broken.

Do not use where directl

NOTES

Rated life based on 11 hours per start

Sep 27, 2017 6:38:23 PM For additional information, visit www.gelighting.com