

46746 - F39W/T5/841/ECO

GE Ecolux® Starcoat® T5


• Passes TCLP, which can lower disposal costs.

a product of

ecomagination







CAUTIONS & WARNINGS

Caution


- Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

Warning


- Risk of Electric Shock
- Turn power off before inspection, installation or removal.

GRAPHS & CHARTS

Graphs_Lumen Maintenance



Graphs_Lamp Mortality



GENERAL CHARACTERISTICS

Lamp Type Linear Fluorescent - Straight

Bulb

Base Miniature Bi-Pin (G5)

Rated Life 30000.0 hrs

Rated Life (rapid start) @ Time 30000.0 @ 3.0/36000.0 @

12.0 h

Soda lime **Bulb Material** Starting Temperature (MIN) -20.0 °C

LEED-EB MR Credit 26 picograms Hg per mean

lumen hour

Additional Info TCLP compliant **Primary Application** Full Wattage

PHOTOMETRIC CHARACTERISTICS

Initial Lumens 3500.0 Mean Lumens 3220.0 Nominal Initial Lumens per Watt 89 Color Temperature 4100.0 K Color Rendering Index (CRI) 85.0 S/P Ratio (Scotopic/Photopic 1.7

Ratio)

ELECTRICAL CHARACTERISTICS

Wattage Voltage 112.0

350 V @ 10 °C Open Circuit Voltage (rapid

start) Min @ Temperature

Cathode Resistance Ratio - Rh/ 4.25 Rc (MIN) Cathode Resistance Ratio - Rh/ 6.5 Rc (MAX)

Current Crest Factor (MAX) 1.7

DIMENSIONS

Maximum Overall Length 33.4000 in(848.4 mm)

(MOL)

Nominal Length 33.400 in(848.4 mm) Bulb Diameter (DIA) (MAX) 0.670 in(17.0 mm) Bulb Diameter (DIA) 0.625 in(15.9 mm) Max Base Face to Base Face 33.430 in(849.1 mm)

(A)

Face to End of Opposing Pin 33.610 in(853.7 mm)

(B) (MIN)

Face to End of Opposing Pin 33.700 in(856.0 mm)

(B) (MAX)

PRODUCT INFORMATION

Product Code 46746

Description F39W/T5/841/ECO

Standard Package Case

Standard Package GTIN 10043168467466

Standard Package Quantity 40 Sales Unit Unit No Of Items Per Sales Unit No Of Items Per Standard 40

Package

UPC 043168467469

Graphs_Spectral Power Distribution

