




VAPOR BARRIER NON-METALLIC CABLE BOXES

4 in. Round Vapor Barrier Ceiling Fan Box
2-5/8 in. Deep, 12.5 Cu. in.

A83



Catalog #: 7120VB

APPLICATIONS

RACO® Nonmetallic cable boxes are used in branch circuit wiring to splice wires
 Provide excellent protection for wiring system or devices
 Vapor barrier boxes prevent unwanted penetration of exterior air and help maintain the existing interior environment from elements outside the structure
 RACO® nonmetallic vapor barrier cable boxes provide the installer with a cost alternative that is lightweight and east to install and provide excellent protection for wiring system or devices
 RACO® Nonmetallic cable boxes are used in branch circuit wiring to splice wires and accommodates wiring devices such as switches and receptacle

PRODUCT FEATURES

RACO® Nonmetallic cable boxes provide the installer with a cost alternative that is lightweight and easy to install
 Self-clamping wire entry clamps
 Round fixture boxes offer an optional front-mounted grounding screw
 For use wherever fans (Cat. #7120, 7120-1, 7120VB only) or lighting canopies are to be installed
 Vapor/air barrier flange and integral wire entry seal provides superior energy savings and quick installation
 Hands free installation for 1/2", 5/8", or 3/4" drywall
 Front mounted grounding screw with combination straight/Robertson head
 Unique saddle design straddles standard joists
 Fits ant 1-1/2" wide joist

UL LISTED

File E 195963

COMPLIANCES

Boxes are listed for Applications (Electrical Codes), UL Green Book
 Boxes are listed for mechanical properties, including the 2-hour Fire Rating, (building codes) UL Orange Book
 Federal Manufacturer's number 28488

FIRE RESISTANCE

2-hour fire rating, UL Orange Book

US PATENTS

5234119

OTHER PATENTS

Mexico 179,825

GENERAL PRODUCT INFORMATION

Wiring System: Nonmetallic Sheathed Cable
 Color: Black

RECOMMENDED MAX LOAD

Ceiling Fan (Dynamic) Lbs.: 70
 Fixture (Static) Lbs.: 210

CONFIGURATION

Cable Clamps: 4
 Side Knockout(s): ---
 Bottom Knockouts(s): ---

DRAWING DIMENSIONS

Dimension A: 2-5/8 in.

PRODUCT MEASUREMENTS

Depth: 2-5/8 in.
 Cubic Inches (cm3): 12.5 (204.8)
 Wt. Ea. (Lbs.): 0.258

Product Length (in.): 2.60
Product Width (in.): 5.15
Product Height (in.): 5.15

PACKAGING

Minimum Pack Qty.: 24
Std. Pkg.: 24
Product UPC-A Labeled: Yes
Weight (Lbs. Per/C): 25.80
Ship Carton Length (in.): 16.13
Ship Carton Width (in.): 6.63
Ship Carton Height (in.): 11.00
Ctn Weight (Lbs.): 6.19
Pallet Qty: 1584
UPC Number: 050169999714
I2of5: 50050169999719