



## Concrete Ring, Welded, 3 in. Deep, Single Row 3/4 in. & 1 in. KO's

By Raco  
Catalog # 277

Concrete Ring, Welded, 3 in. Deep, Single Row 3/4 in. & 1 in. KO's



### Features

- Flat sides provide excellent contact for locknuts
- External ears are used to nail the ring to the wood form
- Top cover is removable for before-pour work
- Ears on inside of box are for fixtures
- Waxed fixture ears prevent concrete from interfering with the threads
- A variety of covers are available
- Cover plate must be ordered separately with all RACO® concrete rings

### General

Drawn or Welded	Welded
EU RoHS Indicator	Contact Manufacturer
Knockouts	3/4 in;1 in
Material	Steel
Type	Concrete Ring
UPC	050169002773
Wiring System	Conduit

### Dimensions

Cubic Capacity	37 cu.in
Depth	3 in
Fixture Lbs.	50 lb
Height	4 in
Weight	0.79 lb
Width	4 in

### Certifications And Compliance

Certified Listed	UL Listed
------------------	-----------

### Logistics

Carton Quantity	25
Packaging Type	No Packaging
Pallet Quantity	1350

### Product Assets

[Catalogs - RACO / TayMac / Bell Full Catalog](#)  
[Certifications - UL COC - E195978-18](#)  
[Certifications - LEED Statement](#)  
[Certifications - NEMA OS1](#)  
[Certifications - UL COC - E195978- 3](#)  
[SDS - HCC\\_SDS](#)  
[Terms and Conditions - HCC Terms & Conditions](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
RACO-277-SPEC-EN | REV 5/2024