

Products

- > [Index](#)
- > [Featured Products](#)
- > [Cross Reference](#)
- > [UPC Search](#)

**Product Datasheet**

[Catalog Home](#) [Home Page](#)

[Search](#)

**238 -- 4" Square Box, 2-1/8" Deep, 1/2" & 3/4" Side Knockouts, Metal Stud Bracket, Welded**



**Product Specifications**

<b>Box Type</b>	RACO Steel Boxes & Covers
<b>Box Family</b>	4" Square Boxes, Covers, Extension Rings
<b>Box Category</b>	4" Square Boxes - For Conduit
<b>Category</b>	4" Square Box
<b>Wiring System</b>	Conduit
<b>Box Depth</b>	2-1/8"
<b>Side Knockout(s)</b>	8, 1/2" & 4, TKO
<b>Bottom Knockout(s)</b>	3, 1/2" & 2, TKO
<b>Bracket Type</b>	BOX-LOC, For metal studs
<b>Bracket Setback</b>	Flush
<b>Drawn or Welded</b>	Welded
<b>Cubic Inch Capacity</b>	30.3
<b>UPC Number</b>	050169002384
<b>Product UPC-A Labeled</b>	Yes
<b>Minimum Pack Qty.</b>	25
<b>Carton UPC Bar Code</b>	050169992388
<b>Inner Leaf 2 of 5 Bar Code</b>	50050169002389
<b>Unit Carton Quantity</b>	25
<b>Ship Carton Length (In.)</b>	20.25
<b>Ship Carton Width (In.)</b>	10.25
<b>Ship Carton Height (In.)</b>	8.5
<b>Weight (Per/C)</b>	105.2
<b>Pallet Quantity</b>	1250
<b>Fire Resistance</b>	Acceptable for use in 2-hour rated walls
<b>Dimension A</b>	2-1/8"
<b>Dimension B</b>	4-5/8"

**Dimension C**

5-1/2"

**Applications**

- Boxes are installed in ceilings or walls for lighting fixtures, switches or receptacles
- Square boxes are used where multiple conductor runs are split into two or more directions to bring power to a number of electrical devices

**Product Features**

- Features RACO's patented TKO 1/2" & 3/4" eccentric knockouts (Per U.L. 514-A, suitable for use without a bonding jumper in circuits above or below 250 volts)
- Combination cover screw heads provide for faster mudring/cover installation
- Features patented BOX-LOC snap-on metal stud bracket for easy installation and positioning on stud
- Covered by U.S. patents 5,408,045 , 4,898,357 & Canada 2,106,801

**Compliances**

UL 514-A listed, File E195978

**Country of Origin**

MADE IN THE U.S.A.

