



## 2 in. Rigid/IMC Sealing Locknut

By Raco  
Catalog # 1208

2 in. Rigid/IMC Sealing Locknut



\*Representative Image

### Features

- All steel construction ensures mechanical protection for the raceway
- Zinc-electroplated for added corrosion protection
- Economical alternative to a threaded enclosure connector
- UL and CSA Listed
- Available in trade sizes 1/2 in. through 4 in.

### General

Conduit Type	Rigid/IMC
EU RoHS Indicator	Contact Manufacturer
Environmental Conditions	Wet Location
Fitting Type	Locknuts
Material	Steel
UPC	050169012086

### Dimensions

Dimensions	0.297 in x 2.906 in x 2.906 in
Height	2.906 in
Length	0.297 in
Trade Size	2 in
Weight	0.05 lb
Width	2.906 in

### Certifications And Compliance

Certified Listed	<ul style="list-style-type: none"><li>• UL Listed</li><li>• CSA Certified</li></ul>
Industry Standard(s)	UL 514B

### Logistics

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	11025

### Product Assets

[Brochures - HCC Products for Solar](#)  
[Catalogs - RACO / TayMac / Bell Full Catalog](#)  
[Certifications - UL COC - E195969-1](#)  
[Product Logo - Conduit](#)  
[SDS - HCC\\_SDS](#)  
[Terms and Conditions - HCC Terms & Conditions](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
RACO-1208-SPEC-EN | REV 5/2024