



## 3/4 in. Rigid/IMC Sealing Locknut

By Raco  
Catalog # 1203

3/4 in. Rigid/IMC Sealing Locknut



\*Representative Image

### Features

- All steel construction ensures mechanical protection for the raceway
- Zinc-electroplated for added corrosion protection
- Economical alternative to a threaded enclosure connector
- UL and CSA Listed
- Available in trade sizes 1/2 in. through 4 in.

### General

Conduit Type	Rigid/IMC
EU RoHS Indicator	Contact Manufacturer
Environmental Conditions	Wet Location
Fitting Type	Locknuts
Material	Steel
UPC	050169012031

### Dimensions

Dimensions	0.235 in x 1.391 in x 1.391 in
Height	1.391 in
Length	0.235 in
Trade Size	3/4 in
Weight	0.029 lb
Width	1.391 in

### Certifications And Compliance

Certified Listed	<ul style="list-style-type: none"><li>• UL Listed</li><li>• CSA Certified</li></ul>
Industry Standard(s)	UL 514B

### Logistics

Carton Quantity	100
Minimum Pack Quantity	100
Pallet Quantity	86400

### Product Assets

[Brochures - HCC Products for Solar](#)  
[Catalogs - RACO / TayMac / Bell Full Catalog](#)  
[Certifications - UL COC - E195969-1](#)  
[Product Logo - Conduit](#)  
[SDS - HCC\\_SDS](#)  
[Terms and Conditions - HCC Terms & Conditions](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
RACO-1203-SPEC-EN | REV 5/2024