



## 4 in. 150 Degree Rigid/IMC Grounding Bushing, Lay-in-Lug, Insulated

By Raco  
Catalog # 1296



\*Representative Image

4 in. 150 Degree Rigid/IMC Grounding Bushing, Lay-in-Lug, Insulated

### Features

- Malleable iron construction ensures mechanical protection
- Zinc-electroplated for added corrosion protection
- Insuliner rated for 150° C
- Grounding Wire Capacity - #6 Str. - #250 MCM
- UL and CSA Listed
- Available in trade sizes of 1/2 in through 4 in.

### General

Conduit Type	Rigid/IMC
Connector Type	Grounding
EU RoHS Indicator	Contact Manufacturer
Fitting Type	Bushings
Insulation Type	Insulated
Material	Malleable Iron
UPC	050169012963

### Dimensions

Dimensions	3.859 in x 4.906 in x 5.703 in
Height	5.703 in
Length	3.859 in
Trade Size	4 in
Weight	1.19 lb
Width	4.906 in

### Electrical Ratings

Grounding Wire Capacity Maximum	#250 MCM
Grounding Wire Capacity Minimum	#6 STR

### Certifications And Compliance

Certified Listed	<ul style="list-style-type: none"><li>• UL Listed</li><li>• CSA Certified</li></ul>
------------------	---

Industry Standard(s)	UL 514B
----------------------	---------

### Logistics

Carton Quantity	5
Minimum Pack Quantity	5
Pallet Quantity	600

### Product Assets

[Catalogs - RACO / TayMac / Bell Full Catalog](#)  
[Certifications - UL COC-E195975-1](#)  
[Product Logo - Conduit](#)  
[SDS - HCC\\_SDS](#)  
[Terms and Conditions - HCC Terms & Conditions](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
RACO-1296-SPEC-EN | REV 5/2024