

Hazardous Location Fittings

Sealing Cement and Fiber for T&B® Sealing Fittings

Cl. I, Div. 1 & 2, Groups C, D
 Cl. II, Div. 1, Groups E, F, G
 Cl. III, Div. 1 & 2

Explosion-Proof
 Dust-Ignition-Proof
 Raintight
 Wet Locations

- Can be used on T&B EYV, EVH series fittings only

Sealing Cement

CAT. NO.	QUANTITY	VOLUME CUBIC INCHES	STD. PKG.	WT. LBS PER 100
EXSC-2	3.2 oz.	2.75	25	20
EXSC-8	13 oz.	11.50	15	81
EXSC-16	1 lb., 10 oz.	23.00	10	163

Packing Fiber

CAT. NO.	QUANTITY	STD. PKG.	WT. LBS PER 100
EXPF-16	1 lb.	1	112

Approximate Amount of Cement and Fiber Required per Hub

CAT. NO.	HUB SIZE	CEMENT QUANTITY	FIBER QUANTITY
EYVF-11	½"	2 oz.	½ oz.
EYVF-22	¾"	3 oz.	⅙ oz.
EYVF-33	1"	4 oz.	⅛ oz.
EVHF-1	½"	2 oz.	½ oz.
EVHF-2	¾"	2 oz.	½ oz.
EVHF-3	1"	4 oz.	¼ oz.
EVHF-4	1¼"	4 oz.	¼ oz.
EVHF-5	1½"	6 oz.	½ oz.
EVHF-6	2"	12 oz.	1 oz.
EVHF-7	2½"	15 oz.	1½ oz.
EVHF-8	3"	40 oz.	2 oz.
EVHF-9	3½"	45 oz.	3 oz.
EVHF-10	4"	50 oz.	4 oz.



EXSC



EXPF