



# 9312-EW



VIDEO

## Product Description

Two gang electrical box for use with nonmetallic sheathed cable

**Brand:** fiberglassBOX™  
**Catalog #:** 9312-EW

**Carton Quantity:** 50  
**Carton Weight:** 25 lb.

**Height:** 3-1/4 in.  
**Width:** 4-1/8 in.  
**Depth:** 2-3/4 in.  
**Volume:** 28 cu. in.  
**Type of Installation:** Old Work  
**Wall Box**  
**Number of Gangs:** 2

**UPC:** 085339291008  
**UNSPSC:** 39121308  
**Country of Origin:** United States of America

## FEATURES

Machine tapped device holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps bulk packed

## APPLICATION

Old work residential construction 2 HR fire resistive walls

## STANDARDS

ANSI / UL 514C: File No. E30594



## FIRE CLASSIFICATION

### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

## COLOR

Beige/tan

## MATERIAL

Fiberglass reinforced polyester BMC

## MOUNTING

Metal wing brackets/metal ears wall compression

## ADDITIONAL MATERIALS

Galvanized steel brackets and plated carbon steel fasteners

Polyvinyl chloride clamps