

Eaton BR1224N125R

Catalog Number: BR1224N125R

Eaton BR convertible loadcenter, No feed-thru lugs, includes BREQS125 hold-down screw, Convertible main, 125 A, B2r, Aluminum, Cover included, NEMA 3R, Metallic, 10 kAIC, BR, 24 Circuits, 12 Spaces, Three-wire, Single-phase, 120/240 V



General specifications

Product Name	Catalog Number
Eaton BR convertible loadcenter	BR1224N125R
UPC	Product Length/Depth
786676448000	5.19 in
Product Height	Product Width
18.75 in	14.31 in
Product Weight	Warranty
34 lb	10 year
Certifications	Catalog Notes
UL 67 UL 50	The maximum rating of the panel is the main breaker rating when used as service entrance equipment. Has notch for brhdk125 hold-down kit.

Product specifications

Number of spaces

12

Special features

No feed-thru lugs, includes BREQS125 hold-down screw

Interrupt rating

10 kAIC

Phase

Single-phase

Wire size

Determined by circuit breaker installed

Bus material

Aluminum

Main circuit breaker

BR

Enclosure

NEMA 3R

Amperage Rating

125 A

Enclosure material

Metallic

Type

Convertible main

Cover

Cover included

Used with

Type BR 1-inch breakers

Number of wires

3

Number of circuits

24

Voltage rating

120/240 V

Box size

B2R

Resources

Brochures

Loadcenters and Circuit Breakers

Type BR Arc Fault Circuit Breakers and Loadcenters

Catalogs

Eaton's Volume 1—Residential and Light Commercial

Drawings

Dimensional Drawing - BR 1 LOADCENTER, BR CONVERTIBLE, OUTDOOR NEMA 3R, 120/240 VAC, 1 PHASE

Installation instructions

Cutler-Hammer Type CH and BR Loadcenters - Instructions

Specifications and datasheets

Eaton Specification Sheet - BR1224N125R



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)