


























## Frame Modules and Modular Connector Fittings

<b>1. Choose Plate Frame</b>	Description	Color	HBL4750 Series		HBL6750 Series	
	Front loading plate will accept any modules in three unit combinations. Angled fixtures to be used in bottom opening only. Use KPIMBZOW/GY plate with modules for HBL4750 and HBL6750 Series device mounting bracket located on page S-45. See section Y for additional Hubbell iSTATION modules and datacom products.	Ivory Gray		<b>IMF1EI</b> <b>IMF1GY</b>		<b>IMF2EI</b> <b>IMF2GY</b>
<i>Note: Each gang accepts 3 module units.</i>						

<b>2. Choose Modules</b>	Color	Catalog Number	Catalog Number	Catalog Number	Catalog Number				
	Ivory Gray	 <b>IMB05EI</b> <b>IMB05GY</b> Blank Module .5 Unit	 <b>IMB1EI</b> <b>IMB1GY</b> Blank Module 1 Unit	 <b>IMB15EI</b> <b>IMB15GY</b> Blank Module 1.5 Unit					
	Ivory Gray	 <b>IM1K1EI</b> <b>IM1K1GY</b> Modular Flat 1 Unit	 <b>IM2K1EI</b> <b>IM2K1GY</b> Modular Flat 1 Unit	 <b>IM1KA15EI</b> <b>IM1KA15GY</b> Modular Angled 1.5 Unit	 <b>IM2KA15EI</b> <b>IM2KA15GY</b> Modular Angled 1.5 Unit				
	Ivory Gray	 <b>IM1SCA15EI</b> <b>IM1SCA15GY</b> SC 1 Duplex Angled, 1.5 Unit	 <b>IM2SCA2EI</b> <b>IM2SCA2GY</b> SC 2 Duplex Angled, 2 Unit	 <b>IM1IA15EI</b> <b>IM1IA15GY</b> Modular Recessed 1.5 Unit	 <b>IM2IA15EI</b> <b>IM2IA15GY</b> Modular Recessed 1.5 Unit				
<b>Keystone Opening</b> Hole size for mounting all Hubbell Jacks. <table style="display: inline-table; vertical-align: middle;"> <tr> <td style="border: 1px solid black; padding: 2px;">A</td> <td style="padding: 2px;">A: .580" (14.73)</td> </tr> <tr> <td style="border: 1px solid black; padding: 2px;">B</td> <td style="padding: 2px;">B: .760" (19.30)</td> </tr> </table>						A	A: .580" (14.73)	B	B: .760" (19.30)
A	A: .580" (14.73)								
B	B: .760" (19.30)								

Modular connectors to be used with any plate with a standard modular opening. Not recommended for use with KP plates. For KP applications use KPIMBZAL/GY bezel and appropriate Hubbell iSTATION modules located in the section Y. See section Y for additional modular connectors.

<b>Modular Connector Fittings</b>	Color	Catalog Number	Catalog Number	Catalog Number
	Ivory Gray	 <b>SFFGEI</b> <b>SFFGGY</b> F-Type Coupler Gold	 <b>SFFEX</b> <b>SFFGX</b> F-Type Coupler Nickel	 <b>SFBE10</b> <b>SFBG10</b> Blank (10 Pack)
	Ivory Gray	 <b>SFRCRFFEI</b> <b>SFRCRFFGY</b> RCA Gold Pass-through F/F Coupler Red Insulator	 <b>SFRCWFFEI</b> <b>SFRCWFFGY</b> RCA Gold Pass-through F/F Coupler White Insulator	 <b>SFRCYFFEI</b> <b>SFRCYFFGY</b> RCA Gold Pass-through F/F Coupler Yellow Insulator
	Black housing only	 <b>SFRC110R</b> RCA 110 Punchdown Red Insulator	 <b>SFRC110W</b> RCA 110 Punchdown White Insulator	 <b>SFRC110Y</b> RCA 110 Punchdown Yellow Insulator
	Black	 <b>SFSV110BK</b> S-Video 110	 <b>SFSVBK</b> S-Video F/F Coupler	 <b>SFSPGBK*</b> <b>SFSPGR**</b> Speaker Post Connector

Note: \*Office white housing with black ring color.  
\*\*Office white housing with red ring color.

<b>Xcelerator Modular Jacks</b>	Color	Catalog Number	Catalog Number	Catalog Number
	Ivory Gray	 <b>HXJ5EEI</b> <b>HXJ5EGY</b> Cat. 5e, T568A, T568B, RJ45	 <b>HXJ6EI</b> <b>HXJ6GY</b> Cat. 6, T568A, T568B, RJ45	 <b>HXJUEI</b> <b>HXJUGY</b> 6 Position USOC, RJ25

Note: See section Y for additional Hubbell Xcelerator modular jacks and colors.

Dimensions in Inches (mm)