

# Metal Raceway

## HBL500 and HBL750 Series

### Elbow and Tee Fittings



	Elbows						
	Description	Color	HBL750 Series	HBL750 Series	Description	Color	HBL500 and HBL750 Series
	<b>Internal Elbow</b> For inside surfaces at right angles.	Ivory White	<b>HBL517IV</b> — A: 3.33" (84.51) B: .58" (14.73) C: 3.33" (84.51)	<b>HBL717IV</b> <b>HBL717W</b> A: 3.33" (84.51) B: .90" (22.86) C: 3.33" (84.51)	<b>Internal Elbow Bend Radius</b> For inside surface at right angles requiring a 1.5" (38.10) bend radius. Suitable for Category 5, 5e, 6 and 6a applications.	Ivory White	<b>HBL5717BRIV</b> — A: 3.33" (84.51) B: .91" (23.11) C: 3.33" (84.51)
	<b>External Elbow</b> For outside surfaces at right angles.	Ivory White	<b>HBL518IV</b> — A: 2.59" (65.71) B: .58" (14.73) C: 2.59" (65.71)	<b>HBL718IV</b> <b>HBL718W</b> A: 2.59" (65.71) B: .90" (22.86) C: 2.59" (65.71)	<b>External Elbow Bend Radius</b> For outside surfaces at right angles requiring a 1.5 in. (38.10) bend radius. Suitable for Category 5, 5e, 6 and 6a applications.	Ivory White	<b>HBL5718BRIV</b> — A: 4.86" (123.43) B: .78" (19.80) C: 1.35" (34.28)
	<b>90° Flat Elbow</b> For right angle turns on same surface.	Ivory White	<b>HBL511IV</b> — A: 2.68" (68.13) B: .61" (15.50) C: 2.68" (68.13)	<b>HBL711IV</b> <b>HBL711W</b> A: 2.68" (68.13) B: .90" (22.86) C: 2.68" (68.13)	<b>Flat Elbow Bend Radius</b> For right angle turns requiring a 1.5 in. (38.10) bend radius. Suitable for Category 5, 5e, 6 and 6a applications.	Ivory White	<b>HBL5711BRIV</b> — A: 3.16" (80.34) B: .91" (23.11) C: 3.16" (80.34)
	<b>45° Flat Elbow</b> For diagonal 45° turns on same surface.	Ivory White	<b>HBL512IV</b> — A: 2.46" (62.61) B: .58" (14.73) C: 2.46" (62.61)	<b>HBL712IV</b> — A: 2.70" (68.49) B: .91" (23.06) C: 2.70" (68.49)	<b>Internal Twisted Elbows</b> For 90° twist with 90° turn. For double turn at right angles from one to another. From a flat run on a side wall to a flat run on a ceiling, edge of door or window trim.	Ivory White  Ivory White	Right Elbow <b>HBL5711RHIV</b> <b>HBL5711RHW</b>  Left Elbow <b>HBL5711LHIV</b> <b>HBL5711LHW</b> A: 2.98" (75.72) B: .94" (23.75) C: 3.00" (76.20)
	<b>Tee Fitting</b> For branches at right angles.	Ivory White	<b>HBL500 and HBL750 Series</b> <b>HBL5715IV</b> <b>HBL5715W</b> A: 3.06" (77.67) B: 1.14" (28.86) C: 3.03" (76.96)	<b>HBL500 and HBL750 Series</b> <b>HBL5715BRIV</b> — A: 5.55" (140.88) B: .90" (22.86) C: 3.16" (80.34)	<b>Tee Fitting Bend Radius</b> For branches at right angles requiring a 1.5 in. (38.10) bend radius. Suitable for Category 5, 5e, 6 and 6a applications.	Ivory White	— A: 5.55" (140.88) B: .90" (22.86) C: 3.16" (80.34)

	Tees						
	Description	Color	HBL500 and HBL750 Series	HBL500 and HBL750 Series	Description	Color	HBL500 and HBL750 Series
	<b>Tee Fitting</b> For branches at right angles.	Ivory White	<b>HBL500 and HBL750 Series</b> <b>HBL5715IV</b> <b>HBL5715W</b> A: 3.06" (77.67) B: 1.14" (28.86) C: 3.03" (76.96)	<b>HBL500 and HBL750 Series</b> <b>HBL5715BRIV</b> — A: 5.55" (140.88) B: .90" (22.86) C: 3.16" (80.34)	<b>Tee Fitting Bend Radius</b> For branches at right angles requiring a 1.5 in. (38.10) bend radius. Suitable for Category 5, 5e, 6 and 6a applications.	Ivory White	— A: 5.55" (140.88) B: .90" (22.86) C: 3.16" (80.34)
	<b>Tee Fitting Bend Radius</b> For branches at right angles requiring a 1.5 in. (38.10) bend radius. Suitable for Category 5, 5e, 6 and 6a applications.	Ivory White	<b>HBL500 and HBL750 Series</b> <b>HBL5715BRIV</b> — A: 5.55" (140.88) B: .90" (22.86) C: 3.16" (80.34)	<b>HBL500 and HBL750 Series</b> <b>HBL5715BRIV</b> — A: 5.55" (140.88) B: .90" (22.86) C: 3.16" (80.34)	<b>Tee Fitting Bend Radius</b> For branches at right angles requiring a 1.5 in. (38.10) bend radius. Suitable for Category 5, 5e, 6 and 6a applications.	Ivory White	— A: 5.55" (140.88) B: .90" (22.86) C: 3.16" (80.34)