


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



PANDUIT PART NO.	RECOMMENDED FASTENER	USE WITH THESE CABLE TIE CROSS SECTIONS	WEIGHT bs 100 (g) pcs		
TMSG3S10	#10 (M5)	M, I, S, LH SG100M,SG150I, SG200S,SG250S,	0.36 (163.3)		
SGTM3S10	SCREW	SG300S, SG370S, SG350LH			







SCALE: FULL

DIMENSIONS IN BRACKETS ARE METRIC [mm]

CAD FILENAME/LAYERS GO3150FL_PB_SGTM3S_00



TINLEY PARK, ILLINOIS

TIE MOUNT FOR SUPER GRIP TIES (SGTM3S10-_ & TMSG3S10-_)

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
(.X) ±0.05 [1.3] (.XXX) ±0.010 [0.25]
(.XX) ±0.02 [0.5] ANGLES ±5°

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.

									(.XX) ±0.02[0.5]	
									JAD	MAT'L:
R	5/22/06	JAD		INITIAL RELEASE (DRAFT)	GB3150FL	R			5/22/06	NY
REV	DATE	BY	СНК	DESCRIPTION	ECN -	R	CUST	SUP	CHK'D	

NYLON 6/6

DRAWING NO.

GB3150FL A