




[Catalog Home](#)

Product Datasheet

ANDERSON FARGO


PT800756 -- Terminal, Pin AL to CU



Bi-Metallic Pin Terminals for Joining Aluminum Conductors to Copper Equipment

Product Specifications

Series Image (Lugs)



PT Series

Aluminum Compression Terminal

Al to CU pigtail

VERSAtile (die and VC tools)

Material	Aluminum Body, Tin Plated Copper Rod
PDF Catalog Page	Click HERE to view the web page.
Plating	No
Inhibitor	Yes
VersaCrimp Conductor Size Minimum	.891 in
VersaCrimp Conductor Size Maximum	1.031 in
Die Type Tooling Crimp Conductor Size Minimum	.964 in
Die Type Tooling Conductor Size Maximum	1.031 in
Lug Conductor Type	AAAC, AAC, ACAR, ACSR, Compact
Crimp Method	VERSAtile (accomodates conventional and Anderson tools)
UL Listed	No
Dimension A	0.75 in
Dimension C	2.875 in (73.15 mm)
Dimension L	6.0 in (152.4 mm)
UPC Code	09635932405
Standard Package	20
Standard Package Unit	Each
Min Order Qty	20
Weight / Ea.	2.127 lbs
Material Type	Non-Standard

Notes


Sleeve connector is factory compressed over knurled surface of tinned annealed copper rod. When used with die type compression tools, use with maximum size conductor only.

Features

Provides a compatible bi-metallic transition for joining aluminum conductor to copper based transformer or other equipment terminals. Prefilled with rubber compatible electrical joint compound and plugged.

Compressed Product Number

PT800756



[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.