



## Main

Product	Double Throw Safety Switch
Current Rating	600 A
Certifications	UL Listed
Enclosure Rating	NEMA 3R galvanized steel
Factory Installed Neutral	None
Disconnect Type	Non-fusible disconnect switch
Mounting Type	Surface
Number of Poles	3
Voltage Rating	600 V AC 600 V DC
Wire Size	250...500 kcmil copper or aluminium

## Complementary

Short-circuit withstand	200 kA
Maximum Horse Power Rating	125 Hp 240 V AC 50...60 Hz 3 phase NEC 430.52 250 Hp at 480 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 350 Hp at 600 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 50 hp 250 V DC
Width	23.66 in (600.96 mm)
Height	63.76 in (1619.50 mm)
Maximum Depth	8.88 in (225.55 mm)
Tightening torque	200 Lbf.In (22.60 N.m) 275 Lbf.In (31.07 N.m) 375 Lbf.In (42.37 N.m) 500 lbf.in (56.49 N.m) 250...500 kcmil)

## Ordering and shipping details

Category	00160 - DE1 MISC
Discount Schedule	DE1
GTIN	00785901568384
Nbr. of units in pkg.	1
Package weight(Lbs)	180 lb(US) (81.65 kg)
Returnability	Yes
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.33 ft (0.406 m)
Package 1 width	3.02 ft (0.919 m)
Package 1 Length	5.71 ft (1.74 m)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------