



**Product Datasheet**



**ANDERSON FARGO**

**GL1351A -- Automatic Splice**



Automatic Splice, 10,000 Lb, for 556.6 Kcmil 26/7 ACSR 'Dove'

**Product Specifications**

<p><b>Splice Type</b></p>	 <p>Automatic Splices</p>
<p><b>Automatic Splice Series</b></p>	 <p>GL-400 Series Automatic Splice Aluminum Full Tension AAC, AAAC &amp; ACSR Conductor Single Layer Al Strand Conductor</p>
<p><b>Conductor Type</b></p>	<p>AAC, AAAC, ACSR</p>
<p><b>Conductor Diameter (Minimum)</b></p>	<p>0.927 in</p>
<p><b>Conductor Diameter (Maximum)</b></p>	<p>0.927 in</p>
<p><b>Automatic Conductor Range</b></p>	<p>652.8 (19) AAAC 556.5 (26/7) ACSR</p>
<p><b>Material</b></p>	<p>Aluminum</p>
<p><b>Gripper Material</b></p>	<p>Aluminum Alloy</p>
<p><b>Minimum Conductor Diameter</b></p>	<p>0.927 in</p>
<p><b>Maximum Conductor Diameter</b></p>	<p>0.927 in</p>
<p><b>Dimension A</b></p>	<p>15 in (370 mm)</p>
<p><b>Dimension B</b></p>	<p>2.0 in (50 mm)</p>
<p><b>UL Listed</b></p>	<p>No</p>
<p><b>Inhibitor Loaded</b></p>	<p>Yes</p>
<p><b>Color Code</b></p>	<p>Natural</p>
<p><b>Material Type</b></p>	<p>Non-Standard</p>
<p><b>UPC Code</b></p>	<p>09635931164</p>
<p><b>Standard Package</b></p>	<p>10</p>
<p><b>Standard Package Unit</b></p>	<p>Each</p>
<p><b>Min Order Qty</b></p>	<p>10</p>
<p><b>Weight / Ea.</b></p>	<p>1.96 lbs</p>

## Notes

Maximum Design Rating 10,000 Lb./44.5 kN, Consult Factory for conductor sizes not listed.

## Features

Individually bagged to seal out dirt before use.

## Compressed Product Number

GL1351A



Ref Dimension A & B



Inside an Automatic Splice.

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

*All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.*

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.