



Dimensions		Inches (mm)		
Style	Rectangular Cover		Round Cover	
				
Box Type				
Standard Box Corrosion-Resistant Box (On-grade)	CFB45G55E –	– CFB45G55CRE	CFB45G55RE –	– CFB45G55RCRE
Recommended Pour Depth	6.00" (152.4)	6.00" (152.4)	6.25" (158.8)	6.25" (158.8)
Min. Depth of Pour	5.50" (139.7)	5.50" (139.7)	6.25" (158.8)	6.25" (158.8)
Adjustability	Fully	Fully	Fully	Fully
Cubic Inch (cm ³) Capacity per Gang	99/105 cu. in.	99/105 cu. in.	99/105 cu. in.	99/105 cu. in.
	(1621/1721 cm ³)	(1621/1721 cm ³)	(1621/1721 cm ³)	(1621/1721 cm ³)
Dimensions – A	5.59" (142.0)	5.59" (142.0)	–	–
Dimensions – B	11.09" (281.6)	11.09" (281.6)	11.09" (281.6)	11.09" (281.6)
Dimensions – C	14.14" (359.2)	14.14" (359.2)	14.14" (359.2)	14.14" (359.2)
Dimensions – D	–	–	8.37" (212.5) TYP.	8.37" (212.5) TYP.
Dimensions – E	5.50" (139.7)	5.50" (139.7)	6.25" (158.8)	6.25" (158.8)
KO Trade Size: Ends Sides Bottom	(2) ¾", 1", 1¼", 2"* (2) ¾", 1", 1¼", 2"* (2) ½", ¾", 1", 1¼"	(2) ¾", 1", 1¼", 2"* (2) ¾", 1", 1¼", 2"* (2) ½", ¾", 1", 1¼"	(2) ¾", 1", 1¼", 2"* (2) ¾", 1", 1¼", 2"* (2) ½", ¾", 1", 1¼"	(2) ¾", 1", 1¼", 2"* (2) ¾", 1", 1¼", 2"* (2) ½", ¾", 1", 1¼"
Cover Style	Rectangular	Rectangular	Round	Round
2 Inch Hub Compatible	Yes	Yes	Yes	Yes

Note: UL File Number E31999. Boxes include concrete covers.

*Requires CFBHUB2 for 2" conduits. CFBHUB200PVC for 2" PVC conduits or CFBHUB125PVC for 1¼" PVC conduits.

Rectangular Covers

- Compatible with CFB45G55E and CFB45G55CRE Series Floor Boxes
- Two large cable egress doors and access 180° opening
- Maximum static load of 1500lb with 2x safety factor**
- Surface style typical applications: carpet, VCT
- Flush style typical applications: tile, finished concrete and terrazzo floors

Finish	Surface Cover Flange Dimensions 11½" x 10"		Flush Cover Flange Dimensions 10½" x 9"	
	Without Insert	With Insert	Without Insert	With Insert
Aluminum Powder Coat	610GCCVRLU	610GCCVRLUC	610GTCVRLU	610GTCVRLUC
Black Powder Coat	610GCCVRBK	610GCCVRBKC	610GTCVRBK	610GTCVRBKC
Brass Powder Coat	610GCCVRBRS	610GCCVRBRSC	610GTCVRBRS	610GTCVRBRSC
Bronze Powder Coat	610GCCVRBRZ	610GCCVRBRZC	610GTCVRBRZ	610GTCVRBRZC
Satin Nickel Powder Coat	610GCCVRNK	610GCCVRNKC	610GTCVRNK	610GTCVRNKC



Round Covers

- Compatible with CFB45G55RE and CFB45G55RCRE Series Floor Boxes
- Maximum static load of 1,000 lbs. with 2x safety factor**
- Recessed covers- 180° access with 2 cable egress doors
- Cover flanges have a 9½ in. diameter and 0.15 in. height

Finish	Surface
Brushed Aluminum	CFBS1R8CVRLU
Black Powder Coated	CFBS1R8CVRBLK
Brass Plated	CFBS1R8CVRBRS
Bronze Plated	CFBS1R8CVRBRZ
Gray Powder Coat	CFBS1R8CVRGRY
Satin Nickel Plated	CFBS1R8CVRNKL



**Load applied through a 3" (76mm) mandrel in center of the cover

ScrubShield®
Complies with UL514 A