20 and 30 Amp 3, 4 and 5 Wire Devices

Wallplates, 1-Gang

Description	Single Receptacles with Face Dia. 1.60" (40.6)
Black nylon, smooth.	P720BK
Stainless steel 302/304, .035 in. (0.9), horizontal brushed finish.	SS720
Brass .04 in. (1.0), horizontal brushed finish.	SB720



P720BK



SS720

Weatherproof Covers

IP44 SUITABILITY

Description	Single Receptacles with Face Dia. 1.60" (40.6)
Cast aluminum, for FS/FD box mounting.	HBL7420
Gray thermoplastic, for FS/FD box mounting, corrosion resistant.	HBL7425WOA
Same as above except yellow.	HBL74CM25WOA



HBL7425WOA

Weatherproof Covers for Flanged Inlets and Flanged Receptacles

IP44 SUITABILITY

Description	Single Receptacles with Face Dia. 1.60" (40.6)
Gray thermoplastic, corrosion resistant.	WP2

Note: Weatherproof covers are UL Listed for wet and damp location with cover closed. Those with suffix WOA are UL Listed with cover open.
See page P-21 for additional information on weatherproof covers.

Closure Cover for 3 Wire Flanged Inlets

Description	Catalog Number
Rubber closure plug.	HBL2899

Note: Closure cover not UL Listed, CSA Certified.



HBL2899

Twist-Lock® Circuit Testers

Description	Rating	20 Amp		30 Amp	
		Configuration	Catalog Number	Configuration	Catalog Number
3-Phase Circuit Tester	3Ø 120/208V AC Min. Volt.: 90V AC	NEMA L21-20P	HBL3PT2511	NEMA L21-30P	HBL3PT2811
Circuit Tester	125V	NEMA L5-20P	HBLT2311	NEMA L5-30P	HBLT2611 HBLT26CM11 (Marine)
	250V	NEMA L6-20P	HBLT2321	NEMA L6-30P	HBLT2621
	277V	NEMA L7-20P	HBLT2331		
	125/250V	NEMA L14-20P	HBLT2411	NEMA L14-30P	HBLT2711
	347V	NEMA L24-20P	HBLT3721		
	128/208V AC	Non-NEMA	HBLT3521		

Note: Testers in other NEMA configurations can be developed upon request.



HBL3PT2511



HBLT26CM11

Single Flush Receptacles

Description	Catalog Number
Removal Bridge, for use with all Twist-Lock EdgeConnect™ receptacles.	HBLSTRB



HBLSTRB

Dimensions in Inches (mm)