

## Combination Switches/Devices

### Features

Mini-toggles provide for multiple switches in a compact single gang. Maximize control while maintaining function and appearance.

- Low profile, less than 1 inch
- Self-grounding feature is standard
- Combination devices provide compact switches in a single-gang opening
- Smooth toggle action
- Multiple-drive Slot/Phillips/Robertson head screws
- Hi-visibility yellow base for easy installation
- Operating temperature: -20°C to 60°C
- UL Listed, CSA Certified



RC108I

### Combination Toggle Switches/Devices

Description	Two (2) Single Pole Switches	Single Pole Switch, Tamper-Resistant, 2 Pole, 3 Wire, Receptacle	Single Pole Switch, 2 Pole, 3 Wire, Receptacle	Single Pole Switch, Pilot Light, Clear Lens, Amber Neon Bulb*
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 120V AC	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V AC
Color				
	Brown <b>RC101</b> Ivory <b>RC101I</b> Light Almond <b>RC101LA</b> White <b>RC101W</b>	Brown <b>RC108TR</b> Ivory <b>RC108ITR</b> Light Almond <b>RC108LATR</b> White <b>RC108WTR</b>	Brown <b>RC108</b> Ivory <b>RC108I</b> Light Almond <b>RC108LA</b> White <b>RC108W</b>	Brown <b>RC109</b> Ivory <b>RC109I</b> Light Almond <b>RC109LA</b> White <b>RC109W</b>

Note: See page Tech-10 for Tamper-Resistant description.  
\*Neutral required for pilot light, see page Z-4 for wiring diagram.

### Combination Toggle Switches/Devices

Description	Single Pole and Three Way Switch	Two (2) Three Way Switches	Three Way Switch, Tamper-Resistant, 2 Pole, 3 Wire, Receptacle	Three Way Switch, 2 Pole, 3 Wire, Receptacle	Three Way Switch, Pilot Light, Clear Lens, Amber Neon Bulb*
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 120V AC	15A 120V AC	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V AC
Color					
	Brown <b>RC103</b> Ivory <b>RC103I</b> Light Almond <b>RC103LA</b> White <b>RC103W</b>	Brown <b>RC303</b> Ivory <b>RC303I</b> Light Almond <b>RC303LA</b> White <b>RC303W</b>	Brown <b>RC308TR</b> Ivory <b>RC308ITR</b> Light Almond <b>RC308LATR</b> White <b>RC308WTR</b>	Brown <b>RC308</b> Ivory <b>RC308I</b> — White <b>RC308W</b>	Brown <b>RC309</b> Ivory <b>RC309I</b> — White <b>RC309W</b>

Note: See page Tech-10 for Tamper-Resistant description.  
\*Neutral required for pilot light, see page Z-4 for wiring diagram.

Dimensions in Inches (mm)