



Weather Resistant Recessed Receptacle with White-In Use Cover

Description	Housing Color	Horizontal Mount	Vertical Mount
Weather and tamper-resistant duplex receptacle with clear white-in-use cover, 15A 125V.	Gray	RW15300GY	RW15400GY
	White	RW15300W	RW15400W
	Brown	RW15300BR	RW15400BR



RW15400GY



Special Use Products

Description	Color	Tamper-Resistant	Tamper-Resistant
Clock Hanger/Recessed Single Receptacle, Tamper-Resistant, 2 pole, 3 wire, grounding, side wire terminations.	Brass Stainless Steel Ivory (Nylon) White (Nylon)	RR151CHBSTR RR151CHSSTR RR151CHITR RR151CHWTR	RR201CHBSTR RR201CHSSTR RR201CHITR RR201CHWTR
Recessed Duplex Receptacle, Tamper-Resistant, 2 pole, 3 wire, grounding, side wire terminations.	Ivory Light Almond White	RR1510I RR1510LA RR1510W	— — —
JLOAD® Multimedia Outlet, Provides power, Cat. 5e and coaxial in a single gang box. Requires RJ600 Box. Includes decorator frame, one Cat. 5e, one F-connector and one power receptacle 125V with voltage dividers*.	Black Gray Ivory Light Almond White	RJ650BKTR RJ650GYTR RJ650ITR RJ650LATR RJ650WTR	RJ620BKTR RJ620GYTR RJ620ITR RJ620LATR RJ620WTR
JLOAD Multimedia Outlet, Includes decorator frame with two open ports for custom configuration and one power receptacle 125V with voltage dividers*.	Black Gray Ivory Light Almond White	RJ65BKTR RJ65GYTR RJ65ITR RJ65LATR RJ65WTR	RJ62BKTR RJ62GYTR RJ62ITR RJ62LATR RJ62WTR
JLOAD Multimedia Box, 3 inches deep with seven 1/2-inch knockouts, non-metallic sheathed cable clamps on each side. Screw in mounting to stud.	Steel	RJ600	RJ600

15A 125V
NEMA 5-15R
UL/CSA20A 125V
NEMA 5-20R
UL/CSA

RR151CHWTR



RR1510W RJ650BKTR



Dividers



RJ600



RS100W



RS101W

In-Line Cord Switches

Description	Mini for use with flat lamp cord.	Heavy duty.
Rating	6A 125V AC	6A 125V AC, 16 HP
Wire	#18 AWG SPT 1 and SPT 2	#18 to #16 AWG SPT 1 and SPT 2
Ivory White	— RS100W	RS101I RS101W

Dimensions in Inches (mm)