



[Catalog Home](#)

Product Datasheet

ANDERSON FARGO

GD519 -- Copper Automatic Dead End



Copper Automatic Dead End, Copper, CW Conductor .45 - .46" (11.5 - 11.8 mm), Clevis Bail

Product Specifications

Category Image



Automatic Deadends

Copper and Aluminum
AAC, AAAC, ACAR, ACSR,
Copper & Copperweld®
Conductor

Series Image (Automatic)



GD-500 Series

Automatic Dead End

Clevis Bail

**Copper & Copperweld®
Conductor**

PDF Catalog Page

[Click HERE to view the web page.](#)

Bail Option

Clevis Bail

Type

Automatic

Material

Copper

Inhibitor Loaded

Yes

Shell Material

Copper Alloy

Bail Material

Galvanized Steel

Clevis Pin Material

Galvanized Steel

Cotter Pin Material

Stainless Steel

Diameter Range

.45 - .46 in (11.5 - 11.8 mm)

Conductor Range Minimum - Maximum

Cu 3/0 str (19), Cu 3/0 str (7), Cu 4/0 sol

Minimum Conductor Diameter

0.45

Maximum Conductor Diameter

0.46

Weight / Ea.

2.2 lbs

Standard Package

25

UPC Code

09635930941

Compressed Product Number

GD519

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.