



## YDS43R45RS

by Burndy  
Catalog ID: YDS43R45RS

Prop 65 Notice

Two-piece, full tension ACSR splice consists of steel inner sleeve and aluminum outer sleeve. ANSI C119.4 Class 1 (Full Tension)

## Product Details

### General

Connector Type	Splice
Die Index	320;319
Die Index - Element A	319
Die Index - Element B	320
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Trade Name	HYSPLICE™
UPC	781810096628
UPC 12 Digit	7818100966288

### Dimensions

Dimension - Aluminum Sleeve Length inch	32.50 in
Dimension - L Length Overall mm	229 mm
Dimension - Length Overall inch	9 in
Dimension - Steel Sleeve Length inch	8 in

### Conductor Related

Conductor - ACSR Str Size	636 (26/7) Grosbeak kcmil
Conductor - ACSR Str Size Range	636 (26/7) Grosbeak kcmil
Conductor - AL Str Size	636(26.7)kcmil
Conductor - AL Str Size Range	636 kcmil
Conductor Type	<ul style="list-style-type: none"> <li>ACSR C Str-Size</li> <li>AL C Str-Size</li> </ul>

### Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No

Standards - RoHS Compliance Status	CM
UL Listed	No

## Logistics

Minimum Pack Quantity	1
-----------------------	---

### For further technical assistance, please contact us

#### **BURNDY Headquarters**

47 East Industrial Park Drive  
Manchester, New Hampshire 03109

#### **Customer Service Hours:**

8 AM - 8 PM Eastern Monday-Friday  
Emergency Service 24-hours/365 Days  
Phone: 1-800-346-4175  
1-603-647-5299 (International)