



Product Number:	51812
Order Abbreviation:	QTP2X26/1X42/32CF/UNVDS
General Description:	QTP2X26/1X42/32CF/UNVDS

Product Information

Abbrev. With Packaging Info.	QTP2X261X4232CFUNVDS 10/CS 1/SKU
Ballast Factor	1
Ballast Height H (in)	1.0630
Ballast Length L (in)	4.9610
Ballast Width W (in)	2.3700
Circuit Type	SERIES
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.00
Nominal Voltage (V)	120.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Open Circuit Voltage (V)	600V
Power Factor	>0.97
Primary Lamp Type	CF26DTE
Sound Rating	A
Starting Method	PROGRAMMED START
Starting Temperature - Fahrenheit	-5
Starting Temperature - Celsius	-20
Total Harmonic Distortion (THD)	<10%
Wiring Method	CONNECTORS
Total Maximum Wattage	60



QUICK60+SM
2 YEAR WARRANTY

QUICKSENSESM

PRO StartTM
PROGRAMMED START

Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- UL Listed Class P, Type 1 Outdoor
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Input Frequency: 50/60Hz.
- Minimum Starting Temperature: -4F/-20C.
- Remote mounting - Typically 6ft with suitable ground plane, but varies by model and application. Contact ECS Application Engineering for information on longer applications.
- High power factor

- Product contains installation instructions