



[Catalog Home](#)

Product Datasheet

CHANCE

M3D62BP -- M3 Switch



14.4kV, 110kV, 600 A, Single-Phase Hookstick Disconnect Switch

Product Specifications

Overhead Product	Single Phase - Distribution Disconnect Switch (Crossarm Mounted)
Voltage(BIL)	15kV (110kV)
Rated Current	600 A
Insulator Type	Porcelain (2 1/4" Bolt Circle)
Base Type	Distribution Base, Serrated Slots
Carriage Bolt Length	8" (203 mm)
Captive Hardware	No
Terminal Connectors (ATC 1343)	Yes
Open Position Latch (160° Opening)	No
Bypass Studs	No
Nominal Voltage	14.4kV
Maximum System Voltage	15.5kV
BIL (LIW)	110kV
Rated 60 Htz Withstand; Dry (Wet)	38kV (30kV)
Maximum 60 Htz Withstand; Dry (Wet)	79kV (---)
Continuous Current Rating	630 A
8hr Emergency Overload	1080 A
Momentary Current Rating	40kA, asymmetrical
Short Time Withstand Current (2 sec)	25kA, symmetrical
Short Time Withstand Current (3 sec)	16kA, symmetrical
Maximum Temperature Rise @ 600A	28°C
Insulator Color	Sky Gray
Leakage Distance (Insulator)	10.5" (266.7mm)
Dry Arcing Distance (Insulator)	6" (152.4mm)

Cantilever (Insulator)	1,200 Lbs (5.34 kN)
Tension (Insulator)	5,000 Lbs (22.24 kN)
Torsion (Insulator)	3,000 in Lbs (339 N-M)
Compression (Insulator)	5,000 Lbs (22.24 kN)
Base Material	Galvanized Steel per ASTM A153
Base Description	Distribution Base, Serrated Slots with four 3/8" Carriage Bolts and backstrap
Dead-ending (Working Load)	8,000 Lbs
Blade(s)	Solid Copper (two blade truss-member)
Hinge(s)	Silver / Silver
Contact(s)	Silver / Silver
Terminal Pads	NEMA two-hole, Tin-plated Copper
Terminal Connector Description	2 - Terminal Connectors (ATC1343, #2 - 500kcmil) w/ galvanized hardware
Governing Standards	All Applicable ANSI/IEEE Standards
Drawing	Click HERE to view drawing of switch
Crated Weight	35.97 lbs
Material Type	Non-Standard
UPC Code	09635904564
Standard Package	1
Standard Package Unit	Each
Min Order Qty	1
Weight / Ea.	35.966 lbs

Compressed Product Number

M3D62BP

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.