

Product data sheet

Characteristics

RUZSF3M

socket RUZ- separate contact -12 A - < 250 V - connector

Product availability : Stock - Normally stocked in distribution facility

Price* : 5.60 USD



Main

Range of product	Zelio Relay
Product or component type	Socket
Contact terminal arrangement	Separate
Product compatibility	Plug-in relay RUM (2 C/O) Plug-in relay RUM (3 C/O)
Shape of pin	Flat
Device short name	RUZ
Sale per indivisible quantity	10

Complementary

[I _{th}] conventional free air thermal current	12 A 5 A with bus jumper
System Voltage	< 250 V
Tightening torque	<= 8.85 lbf.in (1 N.m) (M3.5 screw(s))
Fixing mode	By screw mounting on panel Clip-on mounting on 35 mm symmetrical DIN rail
Marking	CE
Width	1.42 in (36 mm)
Product weight	0.21 lb(US) (0.095 kg)

Environment

Connections - terminals	Connector, flexible cable with cable end 1 x 0.25...1 x 2.5 mm ² / AWG 22...AWG 14 Connector, flexible cable with cable end 2 x 0.25...2 x 1 mm ² / AWG 22...AWG 17 Connector, solid cable without cable end 1 x 0.5...1 x 2.5 mm ² / AWG 20...AWG 14 Connector, solid cable without cable end 2 x 0.5...2 x 1.5 mm ² / AWG 20...AWG 16
Standards	IEC 61984
Product certifications	CSA

UL

Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Ambient air temperature for operation	-40...131 °F (-40...55 °C)
IP degree of protection	IP20 conforming to EN/IEC 60529
Dielectric strength	2500 V

Ordering and shipping details

Category	21128 - ZELIO ICE CUBE RELAY ACCESSORIES
Discount Schedule	CP2
GTIN	00785901582205
Nbr. of units in pkg.	10
Package weight(Lbs)	0.20999999999999999
Returnability	Y
Country of origin	CN

Contractual warranty

Warranty period	18 months
-----------------	-----------