

RPM31BD

power plug-in relay - Zelio RPM - 3 C/O - 24 V DC
- 15 A

Product availability : Stock - Normally stocked in distribution facility



Main

| | |
|--|------------------------------------|
| Range of product | Zelio Relay |
| Series name | Power |
| Product or component type | Plug-in relay |
| Device short name | RPM |
| Contacts type and composition | 3 C/O |
| [Uc] control circuit voltage | 24 V DC |
| [Ithe] conventional enclosed thermal current | 15 A at -40...131 °F (-40...55 °C) |
| Status LED | Without |
| Control type | Lockable test button |
| Utilisation coefficient | 20 % |

Complementary

| | |
|--|---|
| Shape of pin | Flat |
| [Ui] rated insulation voltage | 250 V conforming to IEC 300 V conforming to UL 300 V conforming to CSA |
| [Uimp] rated impulse withstand voltage | 4 kV 1.2/50 µs |
| Contacts material | AgNi |
| [Ie] rated operational current | 15 A at 277 V AC conforming to UL 7.5 A at 28 V DC (NC) conforming to IEC 15 A at 250 V AC (NO) conforming to IEC 7.5 A at 250 V AC (NC) conforming to IEC 15 A at 28 V DC (NO) conforming to IEC 15 A at 28 V DC conforming to UL |
| Maximum switching voltage | 250 V conforming to IEC |
| Load current | 15 A at 250 V AC 15 A at 28 V DC |
| Maximum switching capacity | 3750 VA 420 W |

| | |
|----------------------------------|--|
| Minimum switching capacity | 170 mW at 10 mA, 17 V |
| Operating rate | <= 18000 cycles/hour no-load <= 1200 cycles/hour under load |
| Mechanical durability | 10000000 cycles |
| Electrical durability | 100000 cycles resistive load |
| Average coil consumption | 1.5 W |
| Drop-out voltage threshold | >= 0.1 U _c DC |
| Operating time | 20 ms at nominal voltage |
| Reset time | 20 ms at nominal voltage |
| Rated operational voltage limits | 19.2...26.4 V DC |
| Protection category | RT I |
| Operating position | Any position |
| Safety reliability data | B10d = 100000 |
| Product weight | 0.12 lb(US) (0.054 kg) |
| Device presentation | Complete product |

Environment

| | |
|---------------------------------------|--|
| Dielectric strength | 2000 V AC between coil and contact with reinforced insulation 2000 V AC between poles with basic insulation 1500 V AC between contacts with micro disconnection insulation |
| Standards | CSA C22.2 No 14 UL 508 EN/IEC 61810-1 |
| Product certifications | CSA EAC RoHS REACH UL |
| Ambient air temperature for storage | -40...185 °F (-40...85 °C) |
| Ambient air temperature for operation | -40...131 °F (-40...55 °C) |
| Vibration resistance | 3 gn (f = 10...150 Hz), amplitude +/- 1 mm (on 5 cycles in operation) 5 gn (f = 10...150 Hz), amplitude +/- 1 mm (on 5 cycles not operating) |
| IP degree of protection | IP40 conforming to EN/IEC 60529 |
| Shock resistance | 30 gn not operating 15 gn in operation |
| Pollution degree | 3 |

Ordering and shipping details

| | |
|-----------------------|-------------------------------|
| Category | 21127 - ZELIO ICE CUBE RELAYS |
| Discount Schedule | CP2 |
| GTIN | 00785901572770 |
| Nbr. of units in pkg. | 10 |
| Package weight(Lbs) | 0.12 |
| Returnability | Y |
| Country of origin | CN |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|