



MILBANK
ENERGY AT WORK

S1619-XL



Catalog Number	S1619-XL	Jaw Quantity	4 Terminal
Marketing Product Description	4 Terminal Ringless Small Closing Plate Stud Type	Bypass Type	No Bypass
UPC	784572120730	Number of Meter Positions	1 Position
Length (IN)	4.125	Equipment Ground	Bonded Neutral
Width (IN)	11	Hub Opening	Small Closing Plate
Height (IN)	17	Number Of Receptacles	0
Brand Name	Milbank		
Type	Ringless Meter Socket		
Application	Meter Socket		
Standard	Non UL Listed;Type 3R		
Voltage Rating	600 Volts Alternating Current		
Amperage Rating	200 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	4.125L x 11W x 17H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Overhead or Underground		
Terminal	3/8 Inch Stud		
Insulation	Glass Polyester		
Mounting	Surface Mount		
Enclosure	G90 Galvanized Steel with Powder Coat Finish		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.