



PSC6010341 -- Cutout, Temporary 15Kv



To provide fuse protection during live-line maintenance, the temporary cutout tool simply clamps onto primary conductor with a Grip-All clampstick. Brass stud at lower end accepts clamp on temporary tap jumper. Insulated bushing and hot parts are from Chance Type C-Polymer cutouts: Upper contact with integral sleet shield and hooks for operation by loadbreak tool and lower trunnion of cast bronze. Fusetube must be fitted with fuselink rated no larger than 100 amps.

Product Specifications

Product Type	Jumpers/Load Pick Up
Tool Type	Temporary Cutout Tool
Style	100 Amp Fuse Tube
Voltage Class	15 kV
Main Line Range, Minimum	.162" (4 mm)

Main Line Range, Maximum	1.165" (29.6 mm)
Material Type	Standard
UPC Code	09635902394
Standard Package	1
Standard Package Unit	Each
Min Order Qty	1
Weight / Ea. lbs	11.5 lbs
Operating / Installation Manual	Operating Instructions

Compressed Product Number

PSC6010341

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.