

Eaton XTOB016CC1

Catalog Number: XTOB016CC1

Eaton XT IEC bimetallic overload relay, 12-16A overload range, 45 mm Frame size, 1NO-1NC contact configuration, Direct to contactor mounting, used with 18-32A contactor, 10A trip type



General specifications

Product Name

Eaton XT IEC bimetallic overload relay

Catalog Number

XTOB016CC1

EAN

4015082784522

Product Length/Depth

3.27 in

Product Height

1.89 in

Product Width

1.77 in

Product Weight

0.34 lb

Compliances

RoHS Compliant

CE Marked

ATEX Compliant

Certifications

UL Listed

CSA Certified

IEC 60947

EN 60947

Catalog Notes

Observe the maximum permissible fuse of the contactor with direct device mounting. Suitable for protection of EEx e-motors. EC prototype test certificate available upon request.

defaultTaxonomyAttributeLabel

Overload range

12-16 A

Type

XT IEC Bimetallic Overload Relay

Used with

18-32A contactor

Frame size

45 mm

Contact configuration

1 NO, 1 NC

Mounting

Direct

Trip type

10 A

Resources

Brochures

C440 Electronic Overload Relay

Catalogs

Eaton's Volume 5—Motor Control and Protection

Drawings

XTOB_CC1 AutoCAD 2D Footprint (mm)

XTOB_CC1 AutoCAD 2D Footprint

XTOB_CC1 2D PDF

XTOB_CC1 3D Model Xchange

XTOB_CC1 2D Drawing Xchange

XTOB_CC1 3D Inventor

Multimedia

Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained

Specifications and datasheets

Global Data Sheet - XTOB016CC1

Eaton Specification Sheet - XTOB016CC1



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia