

Eaton XTOB057DC1

Catalog Number: XTOB057DC1

Eaton XT IEC bimetallic overload relay, 40-57A overload range, 55 mm Frame size, 1NO-1NC contact configuration, Direct mounting, used with 50-72A contactor, 10A trip type

General specifications



Photo is representative

Product Name

Eaton XT IEC bimetallic overload relay

Catalog Number

XTOB057DC1

EAN

4015082784591

Product Length/Depth

4.02 in

Product Height

3.12 in

Product Width

2.36 in

Product Weight

0.5 lb

Compliances

CE Marked
RoHS Compliant
ATEX Compliant

Certifications

UL Listed
CSA Certified
IEC 60947
EN 60947

Catalog Notes

Observe the maximum permissible fuse of the contactor with direct device mounting. Suitable for protection of EEx e-motors. EC prototype test certificate available upon request.

defaultTaxonomyAttributeLabel

Overload range

40-57 A

Type

XT IEC Bimetallic Overload Relay

Used with

50-72A contactor

Frame size

55 mm

Contact configuration

1 NO, 1 NC

Mounting

Direct

Trip type

10 A

Resources

Brochures

C440 Electronic Overload Relay

Catalogs

Eaton's Volume 5—Motor Control and Protection

Drawings

XTOB_DC1 2D PDF

XTOB_DC1 AutoCAD 2D Footprint

XTOB_DC1 2D Drawing Xchange

XTOB_DC1 3D Model Xchange

XTOB_DC1 3D Inventor

XTOB_DC1 AutoCAD 2D Footprint (mm)

Multimedia

Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained

Specifications and datasheets

Eaton Specification Sheet - XTOB057DC1

Global Data Sheet - XTOB057DC1



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia