

Eaton XTOB065DC1

Catalog Number: XTOB065DC1

Eaton XT IEC bimetallic overload relay, 50-65A overload range, 55 mm Frame size, 1NO-1NC contact configuration, Direct mounting, used with 65-72A contactor, 10A trip type

General specifications



Product Name

Eaton XT IEC bimetallic overload relay

Catalog Number

XTOB065DC1

EAN

4015082784607

Product Length/Depth

2.36 in

Product Height

3.58 in

Product Width

3.27 in

Product Weight

0.6 lb

Compliances

RoHS Compliant
ATEX Compliant
CE Marked

Certifications

UL Listed
CSA Certified
IEC 60947
EN 60947

Catalog Notes

Observe the maximum permissible fuse of the contactor with direct device mounting. Suitable for protection of EEx e-motors. EC prototype test certificate available upon request.

defaultTaxonomyAttributeLabel

Overload range

50-65 A

Type

XT IEC Bimetallic Overload Relay

Used with

65-72A contactor

Frame size

55 mm

Contact configuration

1 NO, 1 NC

Mounting

Direct

Trip type

10 A

Resources

Brochures

[C440 Electronic Overload Relay](#)

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTOB_DC1 3D Model Xchange](#)

[XTOB_DC1 3D Inventor](#)

[XTOB_DC1 AutoCAD 2D Footprint](#)

[XTOB_DC1 2D Drawing Xchange](#)

[XTOB_DC1 AutoCAD 2D Footprint \(mm\)](#)

[XTOB_DC1 2D PDF](#)

Multimedia

[Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained](#)

Specifications and datasheets

[Eaton Specification Sheet - XTOB065DC1](#)

[Global Data Sheet - XTOB065DC1](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)